

# DIN EN 15207:2015-03 (E)

Tanks for the transport of dangerous goods - Plug/socket connection and supply characteristics for service equipment in hazardous areas with 24 V nominal supply voltage

---

<b>Contents</b>		<b>Page</b>
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>4</b>
<b>4</b>	<b>Power supply characteristics .....</b>	<b>5</b>
<b>4.1</b>	<b>Current ratings of supplies .....</b>	<b>5</b>
<b>4.2</b>	<b>Voltages rating .....</b>	<b>5</b>
<b>5</b>	<b>Design characteristics .....</b>	<b>5</b>
<b>5.1</b>	<b>Plug/socket connection .....</b>	<b>5</b>
<b>5.1.1</b>	<b>General .....</b>	<b>5</b>
<b>5.1.2</b>	<b>Requirements for operation in hazardous areas .....</b>	<b>5</b>
<b>5.1.3</b>	<b>Pin use restriction .....</b>	<b>8</b>
<b>5.1.4</b>	<b>Keying .....</b>	<b>8</b>
<b>5.1.5</b>	<b>Pin assignment .....</b>	<b>8</b>
<b>5.2</b>	<b>Optional additional connections .....</b>	<b>9</b>
<b>5.2.1</b>	<b>General .....</b>	<b>9</b>
<b>5.2.2</b>	<b>Cab socket .....</b>	<b>9</b>
<b>5.3</b>	<b>Ambient operational temperature range .....</b>	<b>9</b>
<b>6</b>	<b>Test .....</b>	<b>9</b>
<b>7</b>	<b>Marking .....</b>	<b>10</b>
<b>7.1</b>	<b>Type plate .....</b>	<b>10</b>
<b>7.2</b>	<b>Warning sign .....</b>	<b>10</b>
<b>Annex A (informative) Example for wiring .....</b>		<b>11</b>
<b>Bibliography .....</b>		<b>13</b>