DIN EN 14620-3:2006-12 (E)

Design and manufacture of site built, verti cal, cylindrical, flat-bottomed steel tanks for the storage of refrigerated, liquefied gases with operating temperatures between 0 °C and -165 °C - Part 3: Concrete components

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 General 5

5 Vapour tightness 6

6 Materials 6
6.1 General 6
6.2 Concrete 6
6.3 Pre-stressing and reinforcing steel 6

7 Design 7
7.1 General 7
7.2 Partial factors for actions and combinations of actions 7
7.3 Liquid tightness 7

8 Detailing provisions 8
8.1 General 8
8.2 Pre-stressing 8
8.3 Wall design 8
8.4 Steel roof liner 8
8.5 Construction joints 8
8.6 Position of tendons and wires 8
8.7 Concrete cover 9
8.8 Minimum reinforcement 9
8.9 Reinforced concrete bund walls 9

9 Construction and workmanship 9
9.1 General 9
9.2 Crack control 9
9.3 Formwork and tie-rods 9
9.4 Spacers 10
9.5 Curing 10
9.6 Tolerances 10

10 Liners and coatings 10
10.1 General 10
10.2 Liners 10
10.3 Coatings 10
10.4 Thermal Protection System (TPS) 11

Annex A (informative) Materials 12

Annex B (informative) Pre-stressed concrete tank 15

Bibliography 21

Figures Figure A.1 -- Notch on reinforcement bar 14

Figure B.1 -- Typical joints for pre-stressed wall and base junction 17

Tables Table 1 -- Partial load factors for accidental actions 7

Table B.1 -- Summary of the advantages and disadvantages of joints in the wall to base junction ... 16