

DIN EN 14620-3:2006-12 (E)

Design and manufacture of site built, vertical, cylindrical, flat-bottomed steel tanks for the storage of refrigerated, liquefied gases with operating temperatures between 0 °C and -165 °C - Part 3: Concrete components

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	General	5
5	Vapour tightness	6
6	Materials	6
6.1	General	6
6.2	Concrete	6
6.3	Pre-stressing and reinforcing steel	6
7	Design	7
7.1	General	7
7.2	Partial factors for actions and combinations of actions	7
7.3	Liquid tightness	7
8	Detailing provisions	8
8.1	General	8
8.2	Pre-stressing	8
8.3	Wall design	8
8.4	Steel roof liner	8
8.5	Construction joints	8
8.6	Position of tendons and wires	8
8.7	Concrete cover	9
8.8	Minimum reinforcement	9
8.9	Reinforced concrete bund walls	9
9	Construction and workmanship	9
9.1	General	9
9.2	Crack control	9
9.3	Formwork and tie-rods	9
9.4	Spacers	10
9.5	Curing	10
9.6	Tolerances	10
10	Liners and coatings	10
10.1	General	10
10.2	Liners	10
10.3	Coatings	10
10.4	Thermal Protection System (TPS)	11
Annex A (informative) Materials		12

Annex B (informative) Pre-stressed concrete tank	15
Bibliography	21
Figures Figure A.1 -- Notch on reinforcement bar	14
Figure B.1 -- Typical joints for pre-stressed wall and base junction	17
Tables Table 1 -- Partial load factors for accidental actions	7
Table B.1 -- Summary of the advantages and disadvantages of joints in the wall to base junction ...	16