

ISO/TR 12767:2007-09 (E)

Measurement of fluid flow by means of pressure differential devices - Guidelines on the effect of departure from the specifications and operating conditions given in ISO 5167

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	2
5 Effect of errors on flowrate calculations	3
5.1 General	3
5.2 Quantifiable effects	3
6 Effects of deviations in construction	4
6.1 Orifice-plate edge sharpness	4
6.2 Thickness of orifice edge	5
6.3 Condition of upstream and downstream faces of orifice plate	6
6.4 Position of pressure tappings for an orifice	6
6.5 Condition of pressure tappings	7
7 Effects of pipeline near the meter	7
7.1 Pipe diameter	7
7.2 Steps and taper sections	8
7.3 Diameter of carrier ring	8
7.4 Undersize joint rings	11
7.5 Protruding welds	11
7.6 Eccentricity	11
8 Effects of pipe layout	14
8.1 General	14
8.2 Discharge coefficient compensation	14
8.3 Pressure tappings	16
8.4 Devices for improving flow conditions	17
9 Operational deviations	17
9.1 General	17
9.2 Deformation of an orifice plate	17
9.3 Deposition on the upstream face of an orifice plate	19
9.4 Deposition in the meter tube	23
9.5 Orifice-plate edge sharpness	23
9.6 Deposition and increase of surface roughness in Venturi tubes	24
10 Pipe roughness	26
10.1 General	26
10.2 Upstream pipe	27
10.3 Downstream pipe	30
10.4 Reduction of roughness effects	30
10.5 Maintenance	30
Bibliography	32