ISO 3354:2008-07 (E)

Measurement of clean water flow in closed conduits - Velocity-area method using current-meters in full conduits and under regular flow conditions

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Terms and symbols 2
3.1 Terms 2
3.2 Symbols 3

4 Principle 4
4.1 General 4
4.2 Measurement of the measuring cross-section 5
4.3 Measurement of local velocities 6
4.4 Location and number of measuring points in the cross-section 7

5 Description of the current-meter 9

6 Requirements for the use of current-meters 9
6.1 Selection of the measuring cross-section 9
6.2 Devices for improving flow conditions 10
6.3 Calibration of the current-meter 11
6.4 Limits of use 11
6.5 Inspection and maintenance of current-meters 13

7 Setting of current-meters into the conduit 13
7.1 Setting of current-meters 13
7.2 Mounting in a circular cross-section 13
7.3 Mounting in a rectangular cross-section 14

8 Determination of the mean axial fluid velocity by graphical integration of the velocity area 16
8.1 General 16
8.2 Circular cross-sections 16
8.3 Rectangular cross-sections 18

9 Determination of the mean axial fluid velocity by numerical integration of the velocity area 20
9.1 General 20
9.2 Circular cross-sections 21
9.3 Rectangular cross-sections 22

10 Determination of the mean axial fluid velocity by arithmetical methods 23
10.1 General 23
10.2 Log-linear method 23
10.3 Log-Chebyshev method 25
11 Uncertainty in the measurement of flow-rate 27
11.1 General 27
11.2 Sources of error in local velocity measurements 27
11.3 Sources of error in estimation of flow-rate 28
11.4 Propagation of errors 29

11.5 Presentation of results 29
11.6 Calculation of uncertainty 30

Annex A (normative) Measuring sections other than circular or rectangular sections 33

Annex B (normative) Corrections for blockage effect 38

Annex C (normative) Recommendations for the selection of the type of current-meter and mounting strut 39

Annex D (normative) Example of measuring point distribution along a radius for velocity measurement in a conduit of circular cross-section in the case of the graphical and numerical methods 41

Annex E (normative) Determination of boundary layer coefficient, m, for extrapolation near the wall 43

Annex F (normative) Definition of terms and procedures used in the uncertainty calculation 45

Annex G (normative) Student's t distribution 48

Annex H (informative) Examples of values of component uncertainties 49

Annex J (informative) Example of calculation of the uncertainty in the flow-rate measurement using current-meters 51