

ISO 3354:2008-07 (E)

Measurement of clean water flow in closed conduits - Velocity-area method using current-meters in full conduits and under regular flow conditions

Contents

Page

Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and symbols	2
3.1 Terms	2
3.2 Symbols	3
4 Principle	4
4.1 General	4
4.2 Measurement of the measuring cross-section	5
4.3 Measurement of local velocities	6
4.4 Location and number of measuring points in the cross-section	7
5 Description of the current-meter	9
6 Requirements for the use of current-meters	9
6.1 Selection of the measuring cross-section	9
6.2 Devices for improving flow conditions	10
6.3 Calibration of the current-meter	11
6.4 Limits of use	11
6.5 Inspection and maintenance of current-meters	13
7 Setting of current-meters into the conduit	13
7.1 Setting of current-meters	13
7.2 Mounting in a circular cross-section	13
7.3 Mounting in a rectangular cross-section	14
8 Determination of the mean axial fluid velocity by graphical integration of the velocity area	16
8.1 General	16
8.2 Circular cross-sections	16
8.3 Rectangular cross-sections	18
9 Determination of the mean axial fluid velocity by numerical integration of the velocity area	20
9.1 General	20
9.2 Circular cross-sections	21
9.3 Rectangular cross-sections	22
10 Determination of the mean axial fluid velocity by arithmetical methods	23
10.1 General	23
10.2 Log-linear method	23
10.3 Log-Chebyshev method	25
11 Uncertainty in the measurement of flow-rate	27
11.1 General	27
11.2 Sources of error in local velocity measurements	27
11.3 Sources of error in estimation of flow-rate	28
11.4 Propagation of errors	29

11.5	Presentation of results	29
11.6	Calculation of uncertainty	30
Annex A (normative) Measuring sections other than circular or rectangular sections		33
Annex B (normative) Corrections for blockage effect		38
Annex C (normative) Recommendations for the selection of the type of current-meter and mounting strut		39
Annex D (normative) Example of measuring point distribution along a radius for velocity measurement in a conduit of circular cross-section in the case of the graphical and numerical methods		41
Annex E (normative) Determination of boundary layer coefficient, m, for extrapolation near the wall		43
Annex F (normative) Definition of terms and procedures used in the uncertainty calculation		45
Annex G (normative) Student's t distribution		48
Annex H (informative) Examples of values of component uncertainties		49
Annex J (informative) Example of calculation of the uncertainty in the flow-rate measurement using current-meters		51