

# ISO 3966:2008-07 (E)

## Measurement of fluid flow in closed conduits - Velocity area method using Pitot static tubes

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
1	Scope .....	1
2	Normative references .....	1
3	Symbols and definitions .....	2
4	Principle .....	4
5	Design of Pitot tubes .....	7
6	Requirements for use of Pitot tubes .....	8
7	Positioning of Pitot tube .....	11
8	Velocity computation .....	11
9	Determination of the discharge velocity by graphical integration of the velocity area .....	14
10	Determination of the discharge velocity by numerical integration of the velocity area .....	17
11	Determination of the discharge velocity by arithmetical methods .....	19
12	Corrections of local velocity measurements .....	23
13	Errors .....	28
Annex A (normative) Pitot tubes .....		34
Annex B (normative) Correction to the measuring position of Pitot tubes used in a transverse velocity gradient .....		39
Annex C (normative) Study concerning turbulence correction .....		41
Annex D (normative) Damping of pressure gauges .....		44
Annex E (normative) Measurements with a Pitot tube in a compressible fluid .....		46
Annex F (normative) Determination of coefficient m for extrapolation near the wall .....		50
Annex G (normative) Example of calculation of the uncertainty on the flow-rate measurement by means of Pitot tubes .....		51
Bibliography .....		54