

# ISO 7194:2008-07 (E)

## Measurement of fluid flow in closed conduits - Velocity-area methods of flow measurement in swirling or asymmetric flow conditions in circular ducts by means of current-meters or Pitot static tubes

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Symbols .....</b>	<b>2</b>
<b>4</b>	<b>Principle .....</b>	<b>2</b>
<b>5</b>	<b>Choice of measuring plane .....</b>	<b>3</b>
<b>6</b>	<b>Devices for improving flow conditions .....</b>	<b>3</b>
<b>7</b>	<b>Measurement of local velocities .....</b>	<b>7</b>
<b>8</b>	<b>Determination of mean flow velocity .....</b>	<b>14</b>
<b>9</b>	<b>Accuracy of flow-rate estimation .....</b>	<b>14</b>
<b>Annex A (normative) Detection and removal of regular pressure fluctuations .....</b>		<b>17</b>
<b>Annex B (normative) Damping of manometers .....</b>		<b>18</b>
<b>Annex C (normative) Calculation of Pitot static tube locations for method B .....</b>		<b>20</b>
<b>Annex D (normative) Corrections to be applied when a Pitot static tube is used .....</b>		<b>22</b>
<b>Annex E (normative) Corrections to be applied when a current-meter is used .....</b>		<b>23</b>
<b>Annex F (normative) Errors due to non-axisymmetrical velocity distribution .....</b>		<b>26</b>
<b>Bibliography .....</b>		<b>27</b>