ISO 3650:1998-12 (E)

Geometrical Product Specifications (GPS) - Length standards - Gauge blocks

Contents

Page

1 Scope 1

2 Normative references 1

3 Definitions 1

4 Nomenclature of faces 3

5 Basis of measurement, traceability, reference condition 4
5.1 Unit of length: metre 4
5.2 Traceability of the length of a gauge block 4
5.3 Reference temperature and standard pressure 4
5.4 Reference orientation of gauge blocks 5

6 General dimensions, material properties, marking 5
6.1 General dimensions 5
6.2 Material properties 5
6.2.1 Material 5
6.2.2 Coefficient of thermal expansion 6
6.2.3 Hardness 6
6.2.4 Dimensional stability 6
6.3 Marking 6

7 Metrological requirements 6
7.1 General 6
7.2 Flatness tolerance, tf 7
7.2.1 Gauge blocks with nominal lengths exceeding 2,5 mm 7
7.2.2 Gauge blocks with nominal lengths up to 2,5 mm 7
7.3 Measuring faces 7
7.4 Side faces 7
7.4.1 Flatness 7
7.4.2 Parallelism 8
7.4.3 Perpendicularity 8
7.4.4 Edges 9

8 Calibration of gauge blocks 9
8.1 General 9
8.2 Wringing test 10
8.3 Measurement by interferometry 10
8.3.1 Measured length 10
8.3.2 Auxiliary plate 10
8.3.3 Corrections to measurements by interferometry 10
8.3.4 Calibration certificate 10
8.4 Measurement by comparison 11
8.4.1 Principle of measurement 11
8.4.2 Central length 11
8.4.3 Method of determining length by comparison 11
8.4.4 Variation in length 11
8.4.5 Corrections 12
8.4.6 Calibration certificate 12

Annex A (informative) Example of a device for the comparison of gauge blocks 13

Annex B (informative) Relation to the GPS matrix model 14

Annex C (informative) Bibliography 15