

ISO 3650:1998-12 (E)

Geometrical Product Specifications (GPS) - Length standards - Gauge blocks

Contents		Page
1	Scope	1
2	Normative references	1
3	Definitions	1
4	Nomenclature of faces	3
5	Basis of measurement, traceability, reference condition	4
5.1	Unit of length: metre	4
5.2	Traceability of the length of a gauge block	4
5.3	Reference temperature and standard pressure	4
5.4	Reference orientation of gauge blocks	5
6	General dimensions, material properties, marking	5
6.1	General dimensions	5
6.2	Material properties	5
6.2.1	Material	5
6.2.2	Coefficient of thermal expansion	6
6.2.3	Hardness	6
6.2.4	Dimensional stability	6
6.3	Marking	6
7	Metrological requirements	6
7.1	General	6
7.2	Flatness tolerance, t_f	7
7.2.1	Gauge blocks with nominal lengths exceeding 2,5 mm	7
7.2.2	Gauge blocks with nominal lengths up to 2,5 mm	7
7.3	Measuring faces	7
7.4	Side faces	7
7.4.1	Flatness	7
7.4.2	Parallelism	8
7.4.3	Perpendicularity	8
7.4.4	Edges	9
8	Calibration of gauge blocks	9
8.1	General	9
8.2	Wringing test	10
8.3	Measurement by interferometry	10
8.3.1	Measured length	10
8.3.2	Auxiliary plate	10
8.3.3	Corrections to measurements by interferometry	10
8.3.4	Calibration certificate	10
8.4	Measurement by comparison	11
8.4.1	Principle of measurement	11
8.4.2	Central length	11
8.4.3	Method of determining length by comparison	11
8.4.4	Variation in length	11
8.4.5	Corrections	12
8.4.6	Calibration certificate	12

Annex A (informative) Example of a device for the comparison of gauge blocks	13
Annex B (informative) Relation to the GPS matrix model	14
Annex C (informative) Bibliography	15