

# ISO 17089-2:2012-10 (E)

## Measurement of fluid flow in closed conduits - Ultrasonic meters for gas - Part 2: Meters for industrial applications

---

Contents	Page
Foreword .....	iv
Introduction .....	v
1 Scope .....	1
2 Normative references .....	1
3 Terms, definitions, and symbols .....	1
3.1 Terms and definitions .....	1
3.2 Symbols and subscripts .....	6
3.3 Abbreviations .....	7
4 Principles of measurement .....	7
4.1 Transit time ultrasonic meters .....	7
4.2 Flare or vent gas meters .....	8
4.3 Factors affecting performance .....	9
4.4 Description of generic types .....	9
4.5 Impact of pressure and temperature on the flowmeter geometry .....	14
4.6 USM measurement uncertainty determination .....	14
4.7 USM classification .....	14
5 Meter characteristics .....	15
5.1 Performance indications .....	15
5.2 Operating conditions .....	15
5.3 Meter body, materials, and construction .....	15
5.4 Connections .....	16
5.5 Dimensions .....	16
5.6 Ultrasonic ports .....	16
5.7 Pressure tapping .....	16
5.8 Anti-roll provision .....	16
5.9 Flow conditioner .....	17
5.10 Markings .....	17
5.11 Transducers .....	17
5.12 Electronics .....	17
5.13 Firmware and software .....	18
5.14 Inspection and verification functions .....	19
5.15 Operation and installation requirements .....	19
5.16 Installation requirements and flow profile considerations .....	21
5.17 Handling and transportation .....	22
6 Test and calibration .....	23
6.1 Flow test and calibration .....	23
6.2 Static testing for leakage and pressure .....	23
6.3 Dimensional measurements .....	23
6.4 Dynamic testing (testing and calibration, adjustment under flowing conditions) .....	25
6.5 Meter diagnostics .....	26
6.6 In situ verification .....	27
Annex A (normative) Special application note on valve characterization and noise .....	29
Bibliography .....	36