

ISO 17089-2:2012-10 (E)

Measurement of fluid flow in closed conduits - Ultrasonic meters for gas - Part 2: Meters for industrial applications

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions, and symbols	1
3.1	Terms and definitions	1
3.2	Symbols and subscripts	6
3.3	Abbreviations	7
4	Principles of measurement	7
4.1	Transit time ultrasonic meters	7
4.2	Flare or vent gas meters	8
4.3	Factors affecting performance	9
4.4	Description of generic types	9
4.5	Impact of pressure and temperature on the flowmeter geometry	14
4.6	USM measurement uncertainty determination	14
4.7	USM classification	14
5	Meter characteristics	15
5.1	Performance indications	15
5.2	Operating conditions	15
5.3	Meter body, materials, and construction	15
5.4	Connections	16
5.5	Dimensions	16
5.6	Ultrasonic ports	16
5.7	Pressure tapping	16
5.8	Anti-roll provision	16
5.9	Flow conditioner	17
5.10	Markings	17
5.11	Transducers	17
5.12	Electronics	17
5.13	Firmware and software	18
5.14	Inspection and verification functions	19
5.15	Operation and installation requirements	19
5.16	Installation requirements and flow profile considerations	21
5.17	Handling and transportation	22
6	Test and calibration	23
6.1	Flow test and calibration	23
6.2	Static testing for leakage and pressure	23
6.3	Dimensional measurements	23
6.4	Dynamic testing (testing and calibration, adjustment under flowing conditions)	25
6.5	Meter diagnostics	26
6.6	In situ verification	27
Annex A (normative) Special application note on valve characterization and noise		29
Bibliography		36