

# ISO/TS 15530-1:2013-09 (E)

## Geometrical product specifications (GPS) - Coordinate measuring machines (CMM): Technique for determining the uncertainty of measurement - Part 1: Overview and metrological characteristics

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Metrological characteristics .....</b>	<b>2</b>
<b>4.1</b>	<b>General .....</b>	<b>2</b>
<b>4.2</b>	<b>Commerce .....</b>	<b>2</b>
<b>4.3</b>	<b>Internal use in an organization .....</b>	<b>2</b>
<b>4.4</b>	<b>Identification, definition, and choice of metrological characteristics .....</b>	<b>2</b>
<b>4.5</b>	<b>Calibration of metrological characteristics .....</b>	<b>3</b>
<b>5</b>	<b>Task-specific uncertainty .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Instrumentation factors .....</b>	<b>4</b>
<b>5.3</b>	<b>Measurement plan factors .....</b>	<b>4</b>
<b>5.4</b>	<b>Extrinsic factors .....</b>	<b>4</b>
<b>6</b>	<b>Techniques to determine task-specific measurement uncertainty components .....</b>	<b>4</b>
<b>6.1</b>	<b>General issues .....</b>	<b>4</b>
<b>6.2</b>	<b>Sensitivity analysis .....</b>	<b>4</b>
<b>6.3</b>	<b>Use of calibrated workpieces or standards (ISO 15530-3) .....</b>	<b>5</b>
<b>6.4</b>	<b>Use of computer simulation (ISO/TS 15530-4) .....</b>	<b>5</b>
<b>Annex A (informative)</b>	<b>Relationship between CMM metrological characteristics, the ISO 10360 series of standards and the ISO 15530 series of standards .....</b>	<b>6</b>
<b>Annex B (informative)</b>	<b>Sources of error and uncertainty of measurement when using a CMM .....</b>	<b>7</b>
<b>Annex C (informative)</b>	<b>Relation to the GPS matrix model .....</b>	<b>12</b>
<b>Bibliography .....</b>		<b>14</b>