ISO 5167-6:2019 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full — Part 6: Wedge meters

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Principles of the method of measurement and computation
- 5 Wedge meters
 - 5.1 Field of application
 - 5.2 General shape
 - 5.3 Material and manufacture
 - 5.4 Pressure tappings
 - 5.5 Discharge coefficient, C
 - 5.5.1 Limits of use
 - 5.5.2 Discharge coefficient of the wedge meter
 - 5.6 Expansibility [expansion] factor, ε
 - 5.7 Uncertainty of the discharge coefficient, C
 - 5.8 Uncertainty of the expansibility [expansion] factor, ε
 - 5.9 Pressure loss
- 6 Installation requirements
 - 6.1 General
 - 6.2 Minimum upstream and downstream straight lengths for installations between various fittings and the wedge meter
 - 6.3 Additional specific installation requirements for wedge meters
 - 6.3.1 Circularity and cylindricality of pipes upstream and downstream of the wedge meter
 - 6.3.2 Roughness of the upstream and downstream pipe
 - 6.3.3 Positioning of a thermowell
 - 6.3.4 Bidirectional wedge meters
- 7 Flow calibration of wedge meters
 - 7.1 General
 - 7.2 Test facility
 - 7.3 Meter installation
 - 7.4 Design of the test programme
 - 7.5 Reporting the calibration results
 - 7.6 Uncertainty analysis of the calibration
 - 7.6.1 General
 - 7.6.2 Uncertainty of the test facility
 - 7.6.3 Uncertainty of the wedge meter
- Annex A (informative) Table of expansibility [expansion] factor
- Annex B (informative) Use of Kd2 parameter

Page count: 13