# ISO 3966:2020 (E)

## Measurement of fluid flow in closed conduits — Velocity area method using Pitot static tubes

# Contents


Foreword

1 Scope

2 Normative references

3 Terms, definitions and symbols

- 3.1 Terms and definitions
- 3.2 Symbols

4 Principle

- 4.1 General principle
- 4.1.1 Graphical integration of the velocity area (see Clause 9)
- 4.1.2 Numerical integration of the velocity area (see Clause 10)
- 4.1.3 Arithmetical methods (see Clause 11)
- 4.2 Measurement of the measuring cross-section
- 4.2.1 Circular cross-sections
- 4.2.2 Rectangular cross-sections
- 4.3 Measurement of local velocities
- 4.3.1 Method of exploring traverse section
- 4.3.2 Reference measurement
- 4.3.3 Checking of velocity distribution
- 4.4 Location and number of measuring points in the cross-section
- 4.4.1 General requirements
- 4.4.2 Circular cross-sections
- 4.4.3 Rectangular cross-sections

5 Design of Pitot tubes

- 5.1 General description
- 5.2 Criteria to be fulfilled by the Pitot tube

6 Requirements for use of Pitot tubes

- 6.1 Selection of the measuring cross-section
- 6.1.1 Location of the measuring cross-section (of selection)
- 6.1.2 Avoidance of asymmetry, swirl and turbulences
- 6.1.3 Maximum flow deviation
- 6.1.4 Preliminary traverse tests
- 6.2 Devices for improving flow conditions
- 6.2.1 Anti-swirl device
- 6.2.2 Profile developer
- 6.2.3 Positioning/Location of devices
- 6.2.4 Provisional guiding installation
- 6.3 Limits of use
- 6.3.1 Nature of the fluid
- 6.3.2 Range of velocities
- 6.3.3 Nature of the flow
- 6.3.4 Dimensional limitations
- 6.3.5 Influence of turbulence
- 6.4 Performance of measurements
- 6.4.1 Measurement of differential pressure
- 6.4.2 Differential pressure fluctuations
- 6.4.3 Determination of fluid density
- 6.5 Inspection and maintenance of the Pitot tube

7 Positioning of Pitot tube

8 Velocity computation

8.1 Verification of conditions for a measurement
8.2 Formulae for velocity computation

9 Determination of the discharge velocity by graphical integration of the velocity area

9.1 Circular cross-section
9.2 Rectangular cross-sections

10 Determination of the discharge velocity by numerical integration of the velocity area

10.1 Circular cross-sections
10.2 Rectangular cross-sections

11 Determination of the discharge velocity by arithmetic methods

11.1 “Log-linear” method
11.1.1 Circular cross-sections
11.1.2 Rectangular cross-sections
11.2 Log-Chebyshev method
11.2.1 Circular cross-sections
11.2.2 Rectangular cross-sections

12 Corrections of local velocity measurements

12.1 Correction for stem blockage
12.1.1 Case where the correction can be neglected
12.1.2 Estimation of the correction of local velocity measurement
12.1.3 Estimation of the overall correction of the flow-rate value (application to arithmetic methods)
12.2 Correction for transverse velocity gradient
12.2.1 Correction for measuring point position
12.2.1.1 Case of graphical or numerical integration
12.2.1.2 Case of arithmetical methods
12.2.2 Overall correction of flow rate
12.3 Correction for turbulence
12.4 Correction for head loss

13 Errors

13.1 Definition of the error
13.2 Errors in the estimation of the local velocity
13.2.1 Random errors
13.2.1.1 Error in the measurement of differential pressure
13.2.1.2 Error due to slow velocity fluctuations
13.2.1.3 Error in density
13.2.1.4 Error in the calculation of the compressibility correction
13.2.2 Systematic errors
13.2.2.1 Error in the Pitot tube calibration
13.2.2.2 Error due to turbulence
13.2.2.3 Error due to the transverse velocity gradient
13.2.2.4 Error due to conduit blockage
13.2.2.5 Error due to the inclination of the Pitot tube with respect to the flow direction
13.2.2.6 Error due to the head loss between total and static pressure tappings
13.3 Errors in the estimation of flow rate
13.3.1 Random errors
13.3.1.1 Error due to local velocity measurements
13.3.1.2 Error due to graph in graphical integration technique
13.3.1.3 Error due to evaluation of power law index, m
13.3.1.4 Error due to positioning Pitot tubes
13.3.2 Systematic errors
13.3.2.1 Error due to measurement of duct dimensions
13.3.2.2 Error due to numerical or arithmetic integration techniques
13.3.2.3 Error due to number of measuring points
13.4 Definition of the standard deviation5 5 The standard deviation as defined here is what is more accurately referred to as the “standard deviation estimation” by statisticians.

13.5 Definition of the tolerance
13.6 Calculation of standard deviation
13.6.1 Standard deviation on local velocity measurement
13.6.2 Standard deviation on flow-rate measurement

Annex A (normative) Pitot tubes

A.1 Different types
A.2 Sensitivity of Pitot tube to inclination

Annex B (normative) Correction to the measuring position of Pitot tubes used in a transverse velocity gradient

B.1 Determination of the displacement of a measuring point
B.2 Determination of the overall correction for flow rate in a circular conduit

Annex C (normative) Study concerning turbulence correction

C.1 Influence of turbulence on the total pressure tap
C.1.1 Pressure probe insensitive to orientation
C.1.2 Pressure probe sensitive to orientation
C.2 Influence of turbulence on the static-pressure tap
C.3 Evaluation of errors for an exploration with a Pitot tube

Annex D (normative) Damping of pressure gauges

D.1 Damping procedure
D.2 Balancing of the damping
D.3 Checking of the damping

Annex E (normative) Measurements with a Pitot tube in a compressible fluid

E.1 General
E.2 List of subscripts used in this annex
E.3 Determination of velocity calculation
E.4 Operating procedure

Annex F (normative) Determination of coefficient m for extrapolation near the wall

F.1 Method of determination of m
F.2 Influence on the calculation of discharge velocity

Annex G (informative) Example of calculation of the uncertainty on the flow-rate measurement by means of Pitot tubes

G.1 Error on the local velocity measurement
G.2 Error on the flow-rate measurement

**Page count: 55**