

DIN EN ISO 5167-3:2021-12 (E)

**Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 3: Nozzles and Venturi nozzles
(ISO 5167-3:2020)**

Contents

| | Page |
|---|------|
| European foreword | 4 |
| Foreword | 5 |
| Introduction | 6 |
| 1 Scope | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 8 |
| 4 Principles of the method of measurement and computation | 8 |
| 5 Nozzles and Venturi nozzles | 9 |
| 5.1 ISA 1932 nozzle | 9 |
| 5.1.1 General shape | 9 |
| 5.1.2 Nozzle profile | 9 |
| 5.1.3 Downstream face | 11 |
| 5.1.4 Material and manufacture | 11 |
| 5.1.5 Pressure tappings | 11 |
| 5.1.6 Coefficients of ISA 1932 nozzles | 13 |
| 5.1.7 Uncertainties | 14 |
| 5.1.8 Pressure loss, | 14 |
| 5.2 Long radius nozzles | 15 |
| 5.2.1 General | 15 |
| 5.2.2 Profile of high-ratio nozzle | 15 |
| 5.2.3 Profile of low-ratio nozzle | 18 |
| 5.2.4 Material and manufacture | 18 |
| 5.2.5 Pressure tappings | 18 |
| 5.2.6 Coefficients of long radius nozzles | 19 |
| 5.2.7 Uncertainties | 19 |
| 5.2.8 Pressure loss, | 20 |
| 5.3 Throat-tapped nozzles | 20 |
| 5.3.1 General | 20 |
| 5.3.2 Profile of throat-tapped nozzle | 20 |
| 5.3.3 Material and manufacturing | 21 |
| 5.3.4 Pressure Tappings | 21 |
| 5.3.5 Coefficients | 22 |
| 5.3.6 Uncertainties | 23 |
| 5.3.7 Calibration and extrapolation | 23 |
| 5.3.8 Pressure Loss | 24 |
| 5.4 Venturi nozzles | 24 |
| 5.4.1 General shape | 24 |
| 5.4.2 Material and manufacture | 27 |
| 5.4.3 Pressure tappings | 27 |
| 5.4.4 Coefficients | 28 |
| 5.4.5 Uncertainties | 29 |
| 5.4.6 Pressure loss | 29 |

| | | |
|---|--|-----------|
| 6 | Installation requirements | 30 |
| 6.1 | General | 30 |
| 6.2 | Minimum upstream and downstream straight lengths for installation between various fittings and the primary device | 30 |
| 6.3 | Flow conditioners | 36 |
| 6.4 | Circularity and cylindricality of the pipe | 36 |
| 6.5 | Location of primary device and carrier rings | 37 |
| 6.6 | Method of fixing and gaskets | 38 |
| 7 | Flow calibration of nozzles | 38 |
| 7.1 | General | 38 |
| 7.2 | Test facility | 39 |
| 7.3 | Meter installation | 39 |
| 7.4 | Design of the test programme | 39 |
| 7.5 | Reporting the calibration results | 39 |
| 7.6 | Uncertainty analysis of the calibration | 39 |
| 7.6.1 | General | 39 |
| 7.6.2 | Uncertainty of the test facility | 39 |
| 7.6.3 | Uncertainty of the nozzle | 40 |
| Annex A (informative) Tables of discharge coefficients and expansibility [expansion] factors | | 41 |
| Annex B (informative) Akashi type (Mitsubishi type) flow conditioner | | 48 |
| Bibliography | | 49 |