

# DIN EN ISO 10360-13:2023-11 (E)

## Geometrical product specifications (GPS ) - Acceptance and reverification tests for coordinate measuring systems (CMS) - Part 13: Optical 3D CMS (ISO 10360-13:2021)

---

| <b>Contents</b>         |  | <b>Page</b> |
|-------------------------|--|-------------|
| European foreword ..... |  | 5           |
| Foreword .....          |  | 6           |
| Introduction .....      |  | 7           |
| <b>1</b>                | <b>Scope .....</b>   | <b>9</b>    |
| <b>2</b>                | <b>Normative references .....</b>  | <b>9</b>    |
| <b>3</b>                | <b>Terms and definitions .....</b>   | <b>9</b>    |
| <b>4</b>                | <b>Symbols .....</b>   | <b>14</b>   |
| <b>5</b>                | <b>Rated operating conditions .....</b>                                      | <b>14</b>   |
| 5.1                     | Environmental conditions .....   | 14          |
| 5.2                     | Operating conditions .....   | 15          |
| 5.2.1                   | General .....  | 15          |
| 5.2.2                   | Material and surface characteristic of material standards .....              | 15          |
| 5.2.3                   | Pre-processing .....   | 16          |
| <b>6</b>                | <b>Acceptance and reverification test .....</b>                              | <b>16</b>   |
| 6.1                     | General .....  | 16          |
| 6.2                     | Distortion characteristics .....   | 16          |
| 6.2.1                   | General .....  | 16          |
| 6.2.2                   | Distortion error .....   | 16          |
| 6.3                     | Probing characteristics .....  | 20          |
| 6.3.1                   | Principle .....  | 20          |
| 6.3.2                   | Material standard .....  | 20          |
| 6.3.3                   | Procedure .....  | 21          |
| 6.3.4                   | Derivation of test results .....   | 21          |
| 6.3.5                   | Flat-form distortion error .....   | 22          |
| 6.4                     | Volumetric length measurement error in concatenated measurement volume ..... | 25          |
| 6.4.1                   | Principle .....  | 25          |
| 6.4.2                   | Material standard .....  | 25          |
| 6.4.3                   | Low CTE case .....   | 25          |
| 6.4.4                   | Procedure .....  | 26          |
| 6.4.5                   | Derivation of test results .....   | 28          |
| <b>7</b>                | <b>Conformity with the specification .....</b>                               | <b>28</b>   |
| 7.1                     | Acceptance test .....  | 28          |
| 7.1.1                   | Acceptance criteria .....  | 28          |
| 7.2                     | Reverification test .....  | 30          |
| <b>8</b>                | <b>Applications .....</b>  | <b>31</b>   |
| 8.1                     | Acceptance test .....  | 31          |
| 8.2                     | Reverification test .....  | 31          |
| 8.3                     | Interim check .....  | 31          |
| <b>9</b>                | <b>Indication in product documentation and data sheets .....</b>             | <b>31</b>   |

|   |           |
|---|-----------|
| <b>Annex A (informative) Evaluation of bi-directional length measurement characteristics .....</b>  | <b>32</b> |
| <b>A.1 General .....</b>  | <b>32</b> |
| <b>A.2 Derivation of bi-directional length measurement test results .....</b>   | <b>32</b> |
| <b>A.2.1 General .....</b>  | <b>32</b> |
| <b>A.2.2 Bi-directional length measurement error compounded from test results based on point cloud .....</b>                                  | <b>32</b> |
| <b>A.3 Indication in product documentation and data sheets .....</b>  | <b>33</b> |
| <b>Annex B (normative) Artefacts that represent a calibrated test length and corresponding measurement procedures .....</b>                   | <b>34</b> |
| <b>B.1 General .....</b>  | <b>34</b> |
| <b>B.2 Artefact and procedure for realizing calibrated test length .....</b>  | <b>35</b> |
| <b>B.2.1 General .....</b>  | <b>35</b> |
| <b>B.2.2 Ball plates or ball bars measured in a centre-to-centre manner by point cloud .....</b>  | <b>35</b> |
| <b>B.2.3 Laser interferometry measured in a centre-to-centre manner .....</b>   | <b>35</b> |
| <b>B.2.4 Step gauges measured in a face-to-face manner .....</b>  | <b>36</b> |
| <b>B.2.5 CMM positioning the gauging surface(s) .....</b>   | <b>36</b> |
| <b>Annex C (informative) Procedure of concatenated length measurement to assess the influence of the concatenation path on error .....</b>    | <b>37</b> |
| <b>C.1 General .....</b>  | <b>37</b> |
| <b>C.2 Concatenated length measurement through detoured concatenation pathway .....</b>   | <b>37</b> |
| <b>C.3 Example of detoured concatenation pathway .....</b>  | <b>38</b> |
| <b>Annex D (informative) Alignment of artefacts .....</b>   | <b>41</b> |
| <b>D.1 General .....</b>  | <b>41</b> |
| <b>D.2 Parallel face artefacts .....</b>  | <b>41</b> |
| <b>D.3 Ball bar .....</b>   | <b>41</b> |
| <b>Annex E (informative) Surface characteristic of material standard .....</b>  | <b>43</b> |
| <b>E.1 General .....</b>  | <b>43</b> |
| <b>E.2 Surface characteristics of material standards potentially impacting measuring performance of optical 3D CMS .....</b>                  | <b>43</b> |
| <b>E.2.1 Colour .....</b>   | <b>43</b> |
| <b>E.2.2 Glossiness .....</b>   | <b>43</b> |
| <b>E.2.3 Roughness .....</b>  | <b>43</b> |
| <b>E.2.4 Other optical characteristics attributed to surface sublayer .....</b>   | <b>44</b> |
| <b>E.2.5 Evaluation of surface characteristics .....</b>  | <b>44</b> |
| <b>E.3 Potential impact behind surface characteristics restricted in the main text of this document .....</b>                                 | <b>44</b> |
| <b>E.4 Possible performance evaluation of optical 3D CMS with influence of surface characteristics of material standards .....</b>            | <b>44</b> |
| <b>E.4.1 Usage of optical spectral transmittancy of colour filter to emulate different surface colour .....</b>                               | <b>44</b> |
| <b>E.4.2 Usage of equivalent optical attenuation means to emulate different surface colour in cases of monochromatic optical 3D CMS .....</b> | <b>45</b> |
| <b>E.4.3 Usage of material standards having identical nominal geometries but different intended surface characteristics .....</b>             | <b>46</b> |
| <b>Annex F (informative) Structural resolution test .....</b>   | <b>47</b> |
| <b>F.1 General .....</b>  | <b>47</b> |
| <b>F.2 Test method .....</b>  | <b>47</b> |
| <b>F.2.1 General .....</b>  | <b>47</b> |
| <b>F.2.2 Structure standard .....</b>   | <b>47</b> |
| <b>F.2.3 Edge structure .....</b>   | <b>48</b> |
| <b>F.2.4 Wave standard .....</b>  | <b>48</b> |

|              |   |           |
|--------------|---|-----------|
| <b>F.3</b>   | <b>Fundamentals</b>   | <b>49</b> |
|              | <b>Annex G (informative) Guidelines for the evaluation of the test value uncertainty</b>  | <b>52</b> |
| <b>G.1</b>   | <b>General</b>  | <b>52</b> |
| <b>G.2</b>   | <b>Terms and definitions</b>  | <b>52</b> |
| <b>G.3</b>   | <b>Test value uncertainty for probing form dispersion errors, <math>u(PForm)</math>, and flat-form distortion errors, <math>u(DForm.Pla)</math></b>                   | <b>52</b> |
| <b>G.3.1</b> | <b>General</b>  | <b>52</b> |
| <b>G.3.2</b> | <b>Form deviation of the test artefact, <math>F</math></b>  | <b>52</b> |
| <b>G.3.3</b> | <b>Standard uncertainty of the form deviation of the reference standard, <math>u(F)</math></b>  | <b>53</b> |
| <b>G.4</b>   | <b>Test value uncertainty of probing size error, <math>u(PSize)</math>, distortion error, <math>u(DCC)</math>, and length measurement error, <math>u(EVol)</math></b> | <b>53</b> |
| <b>G.4.1</b> | <b>General</b>  | <b>53</b> |
| <b>G.4.2</b> | <b>Uncertainty due to the calibration of the reference standard, <math>uCal</math></b>  | <b>54</b> |
| <b>G.4.3</b> | <b>Uncertainty due to the CTE of the reference standard, <math>uCTE</math></b>  | <b>54</b> |
| <b>G.4.4</b> | <b>Uncertainty due to the input temperature of the reference standard, <math>ut</math></b>  | <b>55</b> |
| <b>G.4.5</b> | <b>Uncertainty due to misalignment of the reference standard, <math>uAlign</math></b>   | <b>55</b> |
| <b>G.4.6</b> | <b>Uncertainty of fixturing the reference standard, <math>uFixt</math></b>  | <b>56</b> |
| <b>G.4.7</b> | <b>Uncertainty due to form deviation of the balls of the reference standard, <math>uForm</math></b>   | <b>57</b> |
|              | <b>Annex H (informative) Relation to the GPS matrix model</b>   | <b>59</b> |
| <b>H.1</b>   | <b>General</b>  | <b>59</b> |
| <b>H.2</b>   | <b>Information about this document and its use</b>  | <b>59</b> |
| <b>H.3</b>   | <b>Position in the GPS matrix model</b>   | <b>59</b> |
| <b>H.4</b>   | <b>Related standards</b>  | <b>59</b> |
|              | <b>Bibliography</b>   | <b>60</b> |