

ISO 5167-5:2022-10 (E)

Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full - Part 5: Cone meters

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principles of the method of measurement and computation	2
5 Cone meters	3
5.1 Field of application	3
5.2 General shape	3
5.3 Material and manufacture	7
5.4 Pressure tappings	8
5.5 Discharge coefficient, C	8
5.5.1 Limits of use	8
5.5.2 Discharge coefficient of the cone meter	8
5.6 Expansibility (expansion) factor,	9
5.7 Uncertainty of the discharge coefficient, C	9
5.8 Uncertainty of the expansibility (expansion) factor,	9
5.9 Pressure loss	9
6 Installation requirements	10
6.1 General	10
6.2 Minimum upstream and downstream straight lengths for installations between various fittings and the cone meter	10
6.2.1 General	10
6.2.2 Single 90° bend	11
6.2.3 Two 90° bends in perpendicular planes	11
6.2.4 Concentric expander	11
6.2.5 Partially closed valves	11
6.3 Additional specific installation requirements for cone meters	11
6.3.1 Circularity and cylindricity of the pipe	11
6.3.2 Roughness of the upstream and downstream pipe	11
6.3.3 Positioning of a thermowell	11
7 Flow calibration of cone meters	12
7.1 General	12
7.2 Test facility	12
7.3 Meter installation	12
7.4 Design of the test programme	12
7.5 Reporting the calibration results	13
7.6 Uncertainty analysis of the calibration	13
7.6.1 General	13
7.6.2 Uncertainty of the test facility	13
7.6.3 Uncertainty of the discharge coefficient of the cone meter	13
Annex A (informative) Table of expansibility (expansion) factor	14
Bibliography	15