

ISO/TR 15377:2023-09 (E)

Measurement of fluid flow by means of pressure-differential devices - Guidelines for the specification of orifice plates, nozzles and Venturi tubes beyond the scope of ISO 5167 series

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 1 |
| 5 | Square-edged orifice plates and nozzles: with drain holes, in pipes below 50 mm diameter, and as inlet and outlet devices | 3 |
| 5.1 | Drain holes through the upstream face of the square-edged orifice plate or nozzle | 3 |
| 5.1.1 | General | 3 |
| 5.1.2 | Square-edged orifice plates | 3 |
| 5.1.3 | ISA 1932 nozzles | 5 |
| 5.1.4 | Long radius nozzles | 5 |
| 5.2 | Square-edged orifice plates installed in pipes of diameter 25 mm $D < 50$ mm | 5 |
| 5.2.1 | General | 5 |
| 5.2.2 | Limits of use | 5 |
| 5.2.3 | Discharge coefficients and corresponding uncertainties | 6 |
| 5.3 | No upstream or downstream pipeline | 6 |
| 5.3.1 | General | 6 |
| 5.3.2 | Flow from a large space (no upstream pipeline) into a pipeline or another large space | 6 |
| 5.3.3 | Flow into a large space (no downstream pipeline) | 8 |
| 6 | Orifice plates (except square-edged) | 9 |
| 6.1 | Conical entrance orifice plates | 9 |
| 6.1.1 | General | 9 |
| 6.1.2 | Limits of use | 9 |
| 6.1.3 | Description | 10 |
| 6.1.4 | Pressure tapplings | 13 |
| 6.1.5 | Coefficients and corresponding uncertainties | 13 |
| 6.2 | Quarter-circle orifice plates | 14 |
| 6.2.1 | General | 14 |
| 6.2.2 | Limits of use | 14 |
| 6.2.3 | Description | 15 |
| 6.2.4 | Pressure tapplings | 18 |
| 6.2.5 | Coefficients and corresponding uncertainties | 18 |
| 6.3 | Eccentric orifice plates | 20 |
| 6.3.1 | General | 20 |
| 6.3.2 | Limits of use | 20 |
| 6.3.3 | Description | 20 |
| 6.3.4 | Coefficients and corresponding uncertainties | 23 |
| 7 | Venturi tubes with machined convergent of angle $10,5^\circ$ | 25 |
| 7.1 | General | 25 |
| 7.2 | Description | 25 |
| 7.3 | Limits of use | 25 |

| | | |
|---|--|----|
| 7.4 | Discharge coefficient | 26 |
| 7.5 | Expansibility [expansion] factor | 26 |
| 7.6 | Pressure loss | 26 |
| 7.7 | Installation straight lengths | 26 |
| Annex A (informative) An example of the calculations in 5.1.2 | | 28 |
| Bibliography | | 31 |