ISO/TR 12767:2023-09 (E)

Measurement of fluid flow by means of pressure differential devices - Guidelines on the effect of departure from the specifications and operating conditions given in ISO 5167

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Symbols **2**

5 Effect of errors on flowrate calculations **3**
5.1 General 3
5.2 Quantifiable effects 3

6 Effects of deviations in construction **3**
6.1 Orifice-plate edge sharpness 3
6.2 Thickness of orifice edge 4
6.3 Condition of upstream and downstream faces of orifice plate 5
6.4 Position of pressure tappings for an orifice 6
6.4.1 General 6
6.4.2 Calculation of discharge coefficient 6
6.4.3 Estimation of additional uncertainty 6
6.4.4 Example 6
6.5 Condition of pressure tappings 7

7 Effects of pipeline near the meter **7**
7.1 Pipe diameter 7
7.2 Steps and taper sections 7
7.3 Diameter of carrier ring 8
7.4 Undersize joint rings 11
7.5 Protruding welds 11
7.6 Eccentricity 11

8 Effects of pipe layout **13**
8.1 General 13
8.2 Discharge coefficient compensation 14
8.2.1 Corrections 14
8.2.2 Additional uncertainty 15
8.3 Pressure tappings 16
8.4 Devices for improving flow conditions 16

9 Operational deviations **16**
9.1 General 16
9.2 Deformation of an orifice plate 17
9.2.1 General 17
9.2.2 Elastic deformation 17
9.2.3 Plastic deformation 17
9.3 Deposition on the upstream face of an orifice plate 18
9.4 Deposition in the meter tube 22
9.5 Orifice-plate edge sharpness 23
9.5.1 Deterioration 23
9.5.2 Plate reversal 23
9.6 Deposition and increase of surface roughness in Venturi tubes 24

9.6.1 General 24
9.6.2 Deposition 24
9.6.3 Surface roughness 24

10 Pipe roughness 25
10.1 General 25
10.2 Upstream pipe 26
10.3 Downstream pipe 30
10.4 Reduction of roughness effects 30
10.5 Maintenance 30

Bibliography 32