ISO 3966:2025-07 (E)

Measurement of fluid flow in closed conduits - Velocity area method using Pitot static tubes

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Terms, definitions and symbols 1
3.1 Terms and definitions 1
3.2 Symbols 2

4 Principle 3
4.1 General principle 3
4.1.1 Graphical integration of the velocity area (see Clause 9) 4
4.1.2 Numerical integration of the velocity area (see Clause 10) 4
4.1.3 Arithmetical methods (see Clause 11) 4
4.2 Measurement of the measuring cross-section 4
4.2.1 Circular cross-sections 4
4.2.2 Rectangular cross-sections 4
4.3 Measurement of local velocities 5
4.3.1 Method of exploring traverse section 5
4.3.2 Reference measurement 5
4.3.3 Checking of velocity distribution 5
4.4 Location and number of measuring points in the cross-section 6
4.4.1 General requirements 6
4.4.2 Circular cross-sections 6
4.4.3 Rectangular cross-sections 6

5 Design of Pitot tubes 6
5.1 General description 6
5.2 Criteria to be fulfilled by the Pitot tube 7

6 Requirements for use of Pitot tubes 8
6.1 Selection of the measuring cross-section 8
6.1.1 Location of the measuring cross-section (of selection) 8
6.1.2 Avoidance of asymmetry, swirl and turbulences 8
6.1.3 Maximum flow deviation 8
6.1.4 Measuring cross-sectional velocity distribution 8
6.1.5 Measuring cross-sectional temperature distribution 10
6.1.6 Preliminary traverse tests 10
6.2 Devices for improving flow conditions 10
6.2.1 Anti-swirl device 10
6.2.2 Profile developer 12
6.2.3 Turning vanes 13
6.2.4 Static mixer 14
6.2.5 Positioning/Location of devices 16
6.2.6 Provisional guiding installation 16
6.3 Limits of use 16
6.3.1 Nature of the fluid 16
6.3.2 Range of velocities 16
6.3.3 Nature of the flow 17
6.3.4 Dimensional limitations 17

6.3.5 Influence of turbulence 17
6.4 Performance of measurements 17
6.4.1 Measurement of differential pressure 17
6.4.2 Differential pressure fluctuations 17
6.4.3 Determination of fluid density 18
6.5 Inspection and maintenance of the Pitot tube 18

7 Positioning of Pitot tube 18

8 Velocity computation 18

8.1 Verification of conditions for a measurement 18
8.2 Formulae for velocity computation 19

9 Determination of the discharge velocity by graphical integration of the velocity area 21
9.1 Circular cross-section 21
9.2 Rectangular cross-sections 23

10 Determination of the discharge velocity by numerical integration of the velocity area 24
10.1 Circular cross-sections 25
10.2 Rectangular cross-sections 27

11 Determination of the discharge velocity by arithmetic methods 27
11.1 "Log-linear" method 28
11.1.1 Circular cross-sections 28
11.1.2 Rectangular cross-sections 28
11.2 Log-Chebyshev method 29
11.2.1 Circular cross-sections 29
11.2.2 Rectangular cross-sections 30

12 Corrections of local velocity measurements 31
12.1 Correction for stem blockage 31
12.1.1 Case where the correction can be neglected 31
12.1.2 Estimation of the correction of local velocity measurement 31
12.1.3 Estimation of the overall correction of the flow-rate value (application to arithmetic methods) 32
12.2 Correction for transverse velocity gradient 33
12.2.1 Correction for measuring point position 34
12.2.2 Overall correction of flow rate 34
12.3 Correction for turbulence 35
12.4 Correction for head loss 36

13 Errors 36
13.1 Definition of the error 36
13.2 Errors in the estimation of the local velocity 36
13.2.1 Random errors 36
13.2.2 Systematic errors 37
13.3 Errors in the estimation of flow rate 38
13.3.1 Random errors 38
13.3.2 Systematic errors 38
13.4 Definition of the standard uncertainty 39
13.5 Definition of the expanded uncertainty 39
13.6 Calculation of standard uncertainty 40
13.6.1 Standard uncertainty on local velocity measurement 40
13.6.2 Standard uncertainty on flow-rate measurement 41

Annex A (normative) Pitot tubes 42

Annex B (normative) Correction to the measuring position of Pitot tubes used in a transverse velocity gradient 48

Annex C (normative) Study concerning turbulence correction 50

Annex D (normative) Damping of pressure gauges 53

Annex E (normative) Measurements with a Pitot tube in a compressible fluid 55

Annex F (normative) Determination of coefficient m for extrapolation near the wall 59

Annex G (informative) Example of calculation of the uncertainty on the flow-rate measurement by means of Pitot tubes 60

Bibliography 63