

DIN EN 15664-1:2008-06 (E)

Influence of metallic materials on water intended for human consumption - Dynamic rig test for assessment of metal release - Part 1: Design and operation

Contents		Page
Foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Principle	9
5	Test rig	9
5.1	General	9
5.2	Test rig arrangement	9
5.3	Control line	10
5.4	Test lines	10
5.4.1	General	10
5.4.2	Materials in the form of pipes	10
5.4.3	Materials in the form of test pieces	10
5.5	Reference lines for comparative testing	10
6	Operating conditions	10
6.1	General	10
6.2	Conditioning	11
6.3	Fractional Sampling	11
6.3.1	General	11
6.3.2	Calculation and expression of results for fractional sampling	11
6.3.3	Requirements for the hydraulic function of the test rig	13
6.3.4	Determination of sampling volumes	13
6.4	Normal operation of the test rig	14
7	Test water	14
7.1	Composition	14
7.2	Check of test water	14
8	Sampling	15
8.1	General	15
8.2	Test water sampling	15
8.3	Sampling to determine metal release	15
8.4	Sampling volumes	16
8.4.1	General	16
8.4.2	Test lines with test pieces	16
8.4.3	Test pipes	16
9	Analysis	16
10	Expression of results	16
10.1	Metal concentrations after fixed stagnation time	16
10.2	Equivalent pipe concentration	17
10.3	Mean concentration after a given operating time	17

10.4	Presentation of the test results	17
11	Test report	18
A.1	Test rig	19
Annex A (normative)	Test rig components and assembly	19
A.2	Test piece	21
A.3	Connecting piece	21
B.1	Test rig flow regime and sampling plan (24 h cycle)	23
B.2	Test rig flow regime and sampling plan for 16 h stagnation time	25
C.1	Data on test water composition	26
	Bibliography	31
Annex B (normative) Annex C (normative) Annex D (informative)	Test rig flow regime Test water monitoring and analysis Example of graphs for expression of results	28