DIN EN ISO 1452-2:2010-04 (E)

Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure_- Unplasticized poly(vinyl chloride) (PVC-U)_- Part_2: Pipes (ISO_1452-2:2009)

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols and abbreviated terms 6

4 Material 7
4.1 Pipe material 7
4.2 Density 7
4.3 MRS-value 7

5 General characteristics 7
5.1 Appearance 7
5.2 Colour 7
5.3 Opacity of pipes intended for the above-ground conveyance of water 7

6 Geometrical characteristics 7
6.1 Measurement of dimensions 7
6.2 Nominal outside diameters 7
6.3 Mean outside diameters and their tolerances 8
6.4 Wall thickness and their tolerances 9
6.5 Length of pipe 10
6.6 Pipes with sockets 11
6.7 Pipe ends for ring seal or solvent cement joints 15

7 Classification and selection of pipes 15
7.1 Classification 15
7.2 Selection of nominal pressure and pipe series S for water up to and including 25 °C 15
7.3 Determination of the allowable operating pressure for water up to 45 °C 15

8 Mechanical characteristics 15
8.1 Impact strength 15
8.2 Resistance to internal pressure 16

9 Physical characteristics 17

10 Sealing rings 18

11 Adhesives 18

12 Performance requirements 18

13 Marking 18
13.1 General 18
13.2 Minimum required marking 18
13.3 Additional marking 19

Annex A (normative) **Allowable operating pressures** 20

Annex B (normative) **Imperial (inch)-sized pipes** 22

Bibliography 27