

DIN EN ISO 1452-3:2010-04 (E)

Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) - Part 3: Fittings (ISO 1452-3:2009)

Contents		Page
EN ISO 1452-3:2009 (E) DIN EN ISO 1452-3:2010-04 Foreword		3
Introduction		4
1	Scope	5
2	Normative references	6
3	Terms, definitions, symbols and abbreviated terms	7
3.1	Terms and definitions	7
3.2	Symbols	7
4	Material	7
4.1	Fitting material	7
4.2	Density	7
4.3	MRS-value	8
5	General characteristics	8
5.1	Appearance	8
5.2	Colour	8
5.3	Opacity of fittings intended for the above-ground conveyance of water	8
6	Geometrical characteristics	8
6.1	Measurement of dimensions	8
6.2	Nominal diameters	8
6.3	Fittings for solvent cementing	8
6.4	Adapter fittings	16
6.5	Tapping saddles	18
6.6	Flange adapters and flanges	21
6.7	Elastomeric ring seal fittings	24
6.8	End-load-bearing double-sockets with elastomeric seals	33
7	Classification and operating conditions	33
7.1	Classification	33
7.2	Selection of nominal pressure and pipe series S for water up to and including 25 °C	33
7.3	Determination of the allowable operating pressure for water up to 45 °C	34
8	Mechanical characteristics	34
8.1	Resistance to internal pressure of fittings or parts of fittings	34
8.2	Crushing test	35
9	Physical characteristics	35
10	Sealing rings	36
11	Adhesives	36
12	Performance requirements	36

13	Marking	36
13.1	General	36
13.2	Minimum required marking	36
13.3	Additional marking	37
Annex A (normative) Imperial(inch)-sized fittings		38
Bibliography		41