

ISO 11296-4:2009-11 (E)

Plastics piping systems for renovation of underground non-pressure drain age and sewerage networks - Part 4: Lining with cured-in-place pipes

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	General terms	2
3.2	Techniques	3
4	Symbols and abbreviated terms	4
4.1	Symbols	4
4.2	Abbreviated terms	5
5	Pipes at the "M" stage	5
5.1	Materials	6
5.2	General characteristics	7
5.3	Material characteristics	7
5.4	Geometric characteristics	8
5.5	Mechanical characteristics	8
5.6	Physical characteristics	8
5.7	Jointing	8
5.8	Marking	8
6	Fittings at the "M" stage	8
6.1	Materials	8
6.2	General characteristics	9
6.3	Material characteristics	9
6.4	Geometric characteristics	9
6.5	Mechanical characteristics	10
6.6	Physical characteristics	10
6.7	Jointing	10
6.8	Marking	10
7	Ancillary components	10
8	Fitness for purpose of the installed lining system at the "I" stage	10
8.1	Materials	10
8.2	General characteristics	10
8.3	Material characteristics	11
8.4	Geometric characteristics	11
8.5	Mechanical characteristics	11
8.6	Physical characteristics	13
8.7	Additional characteristics	13
8.8	Sampling	13
9	Installation practice	14
9.1	Preparatory work	14
9.2	Storage, handling and transport of pipe components	14

9.3	Equipment	14
9.4	Installation	15
9.5	Process-related inspection and testing	16
9.6	Lining termination	16
9.7	Reconnecting to existing manholes and laterals	16
9.8	Final inspection and testing	16
9.9	Documentation	16
Annex A (informative) CIPP components and their functions		17
Annex B (normative) Cured-in-place pipes -- Modifications to ISO 178 for flexural testing		18
Annex C (normative) Cured-in-place pipes -- Test method for the determination of long-term flexural modulus under wet conditions		25
Annex D (normative) Cured-in-place pipes -- Determination of the creep factor under dry conditions from a three-point flexural test		29
Bibliography		32