

# ISO 1452-2:2009-12 (E)

## Plastics piping systems for water supply and for buried and above-ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) - Part 2: Pipes

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviated terms .....</b>	<b>2</b>
<b>4</b>	<b>Material .....</b>	<b>3</b>
4.1	Pipe material .....	3
4.2	Density .....	3
4.3	MRS-value .....	3
<b>5</b>	<b>General characteristics .....</b>	<b>3</b>
5.1	Appearance .....	3
5.2	Colour .....	3
5.3	Opacity of pipes intended for the above-ground conveyance of water .....	3
<b>6</b>	<b>Geometrical characteristics .....</b>	<b>3</b>
6.1	Measurement of dimensions .....	3
6.2	Nominal outside diameters .....	3
6.3	Mean outside diameters and their tolerances .....	4
6.4	Wall thickness and their tolerances .....	5
6.5	Length of pipe .....	6
6.6	Pipes with sockets .....	7
6.7	Pipe ends for ring seal or solvent cement joints .....	11
<b>7</b>	<b>Classification and selection of pipes .....</b>	<b>11</b>
7.1	Classification .....	11
7.2	Selection of nominal pressure and pipe series S for water up to and including 25 °C .....	11
7.3	Determination of the allowable operating pressure for water up to 45 °C .....	11
<b>8</b>	<b>Mechanical characteristics .....</b>	<b>11</b>
8.1	Impact strength .....	11
8.2	Resistance to internal pressure .....	12
<b>9</b>	<b>Physical characteristics .....</b>	<b>13</b>
<b>10</b>	<b>Sealing rings .....</b>	<b>14</b>
<b>11</b>	<b>Adhesives .....</b>	<b>14</b>
<b>12</b>	<b>Performance requirements .....</b>	<b>14</b>
<b>13</b>	<b>Marking .....</b>	<b>14</b>
13.1	General .....	14
13.2	Minimum required marking .....	14
13.3	Additional marking .....	15
<b>Annex A (normative)</b>	<b>Allowable operating pressures .....</b>	<b>16</b>

<b>Annex B (normative) Imperial (inch)-sized pipes .....</b>	<b>18</b>
<b>Bibliography .....</b>	<b>23</b>