

ISO 1452-3:2009-12 (E)

Plastics piping systems for water supply and for buried and above -ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) - Part 3: Fittings

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	2
3	Terms, definitions, symbols and abbreviated terms	3
3.1	Terms and definitions	3
3.2	Symbols	3
4	Material	3
4.1	Fitting material	3
4.2	Density	3
4.3	MRS-value	4
5	General characteristics	4
5.1	Appearance	4
5.2	Colour	4
5.3	Opacity of fittings intended for the above-ground conveyance of water	4
6	Geometrical characteristics	4
6.1	Measurement of dimensions	4
6.2	Nominal diameters	4
6.3	Fittings for solvent cementing	4
6.4	Adapter fittings	12
6.5	Tapping saddles	14
6.6	Flange adapters and flanges	17
6.7	Elastomeric ring seal fittings	20
6.8	End-load-bearing double-sockets with elastomeric seals	29
7	Classification and operating conditions	29
7.1	Classification	29
7.2	Selection of nominal pressure and pipe series S for water up to and including 25 °C	29
7.3	Determination of the allowable operating pressure for water up to 45 °C	30
8	Mechanical characteristics	30
8.1	Resistance to internal pressure of fittings or parts of fittings	30
8.2	Crushing test	31
9	Physical characteristics	31
10	Sealing rings	32
11	Adhesives	32
12	Performance requirements	32

13	Marking	32
13.1	General	32
13.2	Minimum required marking	32
13.3	Additional marking	33
Annex A (normative) Imperial(inch)-sized fittings		34
Bibliography		37