

ISO 1452-3:2009-12 (E)

Plastics piping systems for water supply and for buried and above -ground drainage and sewerage under pressure - Unplasticized poly(vinyl chloride) (PVC-U) - Part 3: Fittings

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 2 |
| 3 | Terms, definitions, symbols and abbreviated terms | 3 |
| 3.1 | Terms and definitions | 3 |
| 3.2 | Symbols | 3 |
| 4 | Material | 3 |
| 4.1 | Fitting material | 3 |
| 4.2 | Density | 3 |
| 4.3 | MRS-value | 4 |
| 5 | General characteristics | 4 |
| 5.1 | Appearance | 4 |
| 5.2 | Colour | 4 |
| 5.3 | Opacity of fittings intended for the above-ground conveyance of water | 4 |
| 6 | Geometrical characteristics | 4 |
| 6.1 | Measurement of dimensions | 4 |
| 6.2 | Nominal diameters | 4 |
| 6.3 | Fittings for solvent cementing | 4 |
| 6.4 | Adapter fittings | 12 |
| 6.5 | Tapping saddles | 14 |
| 6.6 | Flange adapters and flanges | 17 |
| 6.7 | Elastomeric ring seal fittings | 20 |
| 6.8 | End-load-bearing double-sockets with elastomeric seals | 29 |
| 7 | Classification and operating conditions | 29 |
| 7.1 | Classification | 29 |
| 7.2 | Selection of nominal pressure and pipe series S for water up to and including 25 °C | 29 |
| 7.3 | Determination of the allowable operating pressure for water up to 45 °C | 30 |
| 8 | Mechanical characteristics | 30 |
| 8.1 | Resistance to internal pressure of fittings or parts of fittings | 30 |
| 8.2 | Crushing test | 31 |
| 9 | Physical characteristics | 31 |
| 10 | Sealing rings | 32 |
| 11 | Adhesives | 32 |
| 12 | Performance requirements | 32 |

| | | |
|--|---------------------------------------|-----------|
| 13 | Marking | 32 |
| 13.1 | General | 32 |
| 13.2 | Minimum required marking | 32 |
| 13.3 | Additional marking | 33 |
| Annex A (normative) Imperial(inch)-sized fittings | | 34 |
| Bibliography | | 37 |