ISO 11298-3:2010-03 (E)

Plastics piping systems for renovation of underground water supply networks - Part 3: Lining with close-fit pipes

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2
3.1 General 2
3.2 Techniques 2
3.3 Geometrics 2
3.4 Materials 2
3.5 Product stages 2
3.6 Service conditions 2
3.7 Joints 3

4 Symbols and abbreviated terms 3
4.1 Symbols 3
4.2 Abbreviated terms 4

5 Pipes at the "M" stage 4
5.1 Materials 4
5.2 General characteristics 4
5.3 Material characteristics 4
5.4 Geometric characteristics 5
5.5 Mechanical characteristics 5
5.6 Physical characteristics 5
5.7 Jointing 5
5.8 Marking 5

6 Fittings at the "M" stage 5

7 Ancillary components 6

8 Fitness for purpose of the installed lining system at the "I" stage 6
8.1 Materials 6
8.2 General characteristics 6
8.3 Material characteristics 6
8.4 Geometric characteristics 6
8.5 Mechanical characteristics 7
8.6 Physical characteristics 8
8.7 Additional characteristics 8
8.8 Sampling 8

9 Installation practice 9
9.1 Preparatory work 9
9.2 Storage, handling and transport 9
9.3 Equipment 9
9.4 Installation 10
9.5 Process-related inspection and testing 11

Annex A (normative) Factory-folded heat-reverted polyethylene (PE) pipe -- Determination of memory ability 12

Bibliography 14