

DIN EN 13598-1:2011-02 (E)

Plastics piping systems for non-pressure underground drainage and sewerage -
Unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE)
- Part 1: Specifications for ancillary fittings including shallow inspection chambers

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms, definitions, symbols and abbreviations	6
3.1	Terms and definitions	6
3.2	Abbreviations	7
4	Material	7
4.1	General	7
4.2	Sealing ring retaining components	8
4.3	Sealing rings	8
4.4	Adhesives for PVC-U	8
5	General characteristics	8
5.1	General	8
5.2	Assemblies	8
5.3	Colour	8
6	Geometrical characteristics	8
6.1	General	8
6.2	Dimensions	9
6.3	Additional requirements	9
7	Types of ancillary fittings	10
8	Physical characteristics	12
9	Mechanical characteristics	13
10	Performance requirements	15
11	Marking	16
11.1	General	16
11.2	Minimum required marking, ancillary fittings	16
11.3	Additional marking	17
Annex A (normative) Reformulated material characteristics used for shallow inspection chambers ..		18
Annex B (normative) Testing sequence and techniques to be used when testing saddles		19
B.1	General	19
B.2	Test equipment	19
B.3	Procedures	20
B.3.1	Resistance to vertical load - Table 3 - pipe stop test	20
B.3.2	Mechanical strength - Table 3	20
B.3.3	Tightness under deformation - Table 6	21
Bibliography		23