ISO 22158:2011-05 (E)

Input/output protocols and electronic interfaces for water meters - Requirements

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Pulse output water meters -- type A 3
4.1 General 3
4.2 Pulse output modes 3
4.3 Pulse waveform definitions 3
4.4 Pulse data set types 3
4.5 Signal output types 8
4.6 Pulse configuration 8

5 Non-addressable water meters -- type B 8
5.1 General 8
5.2 Non-addressable output modes 8
5.3 Non-addressable data set types 9
5.4 Non-addressable V-frame data protocol 10
5.5 Non-addressable two-wire asynchronous mode for reading via an inductive pad and probe 12
5.6 Non-addressable three-wire asynchronous mode for direct connection to the transponder/bus node 13
5.7 Non-addressable two-wire synchronous mode for reading via an inductive pad and probe 14
5.8 Non-addressable three-wire synchronous mode intended for direct connection to the transponder/bus node 15
5.9 Non-addressable two-wire bidirectional asynchronous mode for reading via optocouplers and probe 15
5.10 Compatibility statement 17

6 Addressable water meters -- type C 17
6.1 General 17
6.2 Output mode 1, based on M-bus technology 17
6.3 Output mode 2, based on Dialog technology 29
6.4 Output mode 3, based on NABS technology 39

Annex A (informative) Designation of registration authority 51

Bibliography 52