ISO 25780:2011-05 (E)

Plastics piping systems for pressure and non-pressure water supply, irrigation, drainage or sewerage - Glass-reinforced thermosetting plastics (GRP) systems based on unsaturated polyester (UP) resin - Pipes with flexible joints intended to be inst alled using jacking techniques

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Requirements 11
4.1 Classification 11
4.2 Pipe properties 11
4.3 Materials 12
4.4 Pipe wall construction 13
4.5 Reference conditions for testing 14
4.6 Elapsed time, x, for determination of long-term properties 14
4.7 Joint properties 14

5 Pipes 16
5.1 Geometrical characteristics 16
5.2 Mechanical characteristics 19
5.3 Resistance to strain corrosion 20
5.4 Longitudinal compressive strength 20
5.5 Permissible jacking forces 21
5.6 Specific initial longitudinal compressive modulus, Ec,m 23
5.7 Resistance of pressure pipes to internal pressure 23

6 Marking 23

7 Joint performance 23
7.1 General requirements 23
7.2 Interchangeability 24
7.3 Geometrical characteristics 24
7.4 Design 24
7.5 Performance requirements 24
7.6 Test method additional information 25

Annex A (normative) Plastics piping systems -- Glass-reinforced thermosetting plastics (GRP) pipes -- Determination of the longitudinal compressive properties of a pipe, using a sample of prism test-pieces cut from a ring from the pipe 27

Annex B (normative) Plastics piping systems -- Glass-reinforced thermosetting plastics (GRP) pipes -- Determination of the compressive properties of pipes, using spool test-pieces 34

Annex C (normative) Procedure for the calculation of the permissible jacking force on a GRP-(UP) pipe, Fperm,p 39

Bibliography 51