

ISO 25780:2011-05 (E)

Plastics piping systems for pressure and non-pressure water supply, irrigation, drainage or sewerage - Glass-reinforced thermosetting plastics (GRP) systems based on unsaturated polyester (UP) resin - Pipes with flexible joints intended to be installed using jacking techniques

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Requirements	11
4.1	Classification	11
4.2	Pipe properties	11
4.3	Materials	12
4.4	Pipe wall construction	13
4.5	Reference conditions for testing	14
4.6	Elapsed time, x , for determination of long-term properties	14
4.7	Joint properties	14
5	Pipes	16
5.1	Geometrical characteristics	16
5.2	Mechanical characteristics	19
5.3	Resistance to strain corrosion	20
5.4	Longitudinal compressive strength	20
5.5	Permissible jacking forces	21
5.6	Specific initial longitudinal compressive modulus, $E_{c,m}$	23
5.7	Resistance of pressure pipes to internal pressure	23
6	Marking	23
7	Joint performance	23
7.1	General requirements	23
7.2	Interchangeability	24
7.3	Geometrical characteristics	24
7.4	Design	24
7.5	Performance requirements	24
7.6	Test method additional information	25
Annex A (normative)	Plastics piping systems -- Glass-reinforced thermosetting plastics (GRP) pipes -- Determination of the longitudinal compressive properties of a pipe, using a sample of prism test-pieces cut from a ring from the pipe	27
Annex B (normative)	Plastics piping systems -- Glass-reinforced thermosetting plastics (GRP) pipes -- Determination of the compressive properties of pipes, using spool test-pieces ...	34
Annex C (normative)	Procedure for the calculation of the permissible jacking force on a GRP-(UP) pipe, $F_{perm,p}$	39
Bibliography		51