

ISO 11296-7:2011-11 (E)

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks - Part 7: Lining with spirally-wound pipes

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	3
4.1 Symbols	3
4.2 Abbreviated terms	3
5 Pipes at the "M" stage	3
5.1 Materials	3
5.2 General characteristics	4
5.3 Material characteristics	4
5.4 Geometric characteristics	5
5.5 Mechanical characteristics	6
5.6 Physical characteristics	6
5.7 Jointing	6
5.8 Marking	6
6 Fittings at the "M" stage	7
7 Ancillary components	7
8 Fitness for purpose of the installed lining system at the "I" stage	7
8.1 Materials	7
8.2 General characteristics	7
8.3 Material characteristics	7
8.4 Geometric characteristics	7
8.5 Mechanical characteristics	7
8.6 Physical characteristics	8
8.7 Additional characteristics	8
8.8 Preparation of samples	8
8.9 Adhesives	8
9 Installation practice	8
9.1 Preparatory work	8
9.2 Storage, handling and transportation of profiled plastics strips and fittings	8
9.3 Equipment	8
9.4 Installation	9
9.5 Processrelated inspection and testing	10
9.6 Lining termination	10
9.7 Reconnecting to existing manholes and laterals	10
9.8 Final inspection and testing	10
9.9 Documentation	10

Annex A (normative) Spirallywound pipe -- Test method for watertightness in a deflected condition	11
Annex B (informative) Examples of methods for reconnecting and sealing laterals to SWO pipe	14
Bibliography	16