DIN EN 15934:2012-11 (E)

Sludge, treated biowaste, soil and waste - Calculation of dry matter fraction after determination of dry residue or water content

Contents

Page

Foreword 3

Introduction 4

1 Scope 5

2 Normative references 5

3 Terms and definitions 5

4 Principle 5
4.1 General 5
4.2 Principle of Method A -- Drying at 105 °C (dry residue) 6
4.3 Principle of Method B -- Direct Karl-Fischer-titration (water content) 6

5 Sample preparation 6

6 Method A -- Drying at 105 °C 6
6.1 General 6
6.2 Interferences 6
6.3 Hazards 6
6.4 Apparatus 6
6.5 Procedure 7
6.6 Calculation of results 7

7 Method B -- Direct Karl-Fischer-titration (volumetric/coulometric detection) 8
7.1 Interferences 8
7.2 Reagents 8
7.3 Apparatus 8
7.4 Procedure 8
7.4.1 Determination of the equivalence factor 8
7.4.2 Analysis of liquid samples 9
7.4.3 Analysis of solid samples 9

8 Calculation of dry matter fraction 10

9 Precision 10

10 Test report 10

Annex A (informative) Repeatability and reproducibility 11

A.1 Performance characteristics 11
A.2 Types of samples and sample preparation 12
A.3 Homogeneity and stability 13
A.4 Dry matter fraction results by different methods 14

Annex B (informative) Azeotropic distillation with toluene 15

B.1 General 15
B.2 Interferences 15

B.3 Hazards 15
B.4 Reagents 15
B.5 Apparatus 15
B.6 Procedure 16
B.7 Calculation of results 16
B.8 System performance check 16
B.9 Performance data 17

Annex C (informative) Summary of general requirements and recommendations 19