

DIN EN 12842:2012-11 (E)

Ductile iron fittings for PVC-U or PE piping systems - Requirements and test methods

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	5
3	Terms and definitions	5
4	Technical requirements	8
4.1	General	8
4.2	Dimensional requirements	10
4.3	Material characteristics	12
4.4	Coatings	13
4.5	Marking	14
4.6	Leak tightness	14
5	Performance requirements for joints	14
5.1	General	14
5.2	Leak tightness of flexible joints	15
5.3	Long term hydrostatic strength test	17
5.4	Flanged joints	19
6	Test methods	19
6.1	Tensile testing for ductile iron	19
6.2	Brinell hardness for ductile iron	20
6.3	Works leak tightness test	21
7	Performance tests	21
7.1	Leak tightness of joints to internal hydrostatic pressure	21
7.2	Leak tightness of joints to negative internal pressure	23
7.3	Leak tightness of joints to dynamic internal pressure	24
7.4	Long term hydrostatic strength test for joints of fittings for PE pipes	24
7.5	Pull out test at 25 °C for restrained joints for PE pipes	25
7.6	Long term hydrostatic strength test for joints of fittings for PVC-U pipe	25
8	Tables of dimensions	26
8.1	Dimensions of sockets for push-in flexible joints	26
8.2	Dimensions of sockets for mechanical flexible joints	28
8.3	Dimensions of fittings	29
9	Evaluation of conformity	44
9.1	General	44
9.2	Initial performance testing	45
9.3	Factory production control (FPC)	46
Bibliography		49