

# DIN EN 295-1:2013-05 (E)

## Vitrified clay pipe systems for drains and sewers - Part 1: Requirements for pipes, fittings and joints

---

Contents	Page
<b>Foreword .....</b>	<b>4</b>
<b>1 Scope .....</b>	<b>6</b>
<b>2 Normative references .....</b>	<b>6</b>
<b>3 Terms and definitions .....</b>	<b>6</b>
<b>4 Symbols and abbreviations .....</b>	<b>7</b>
<b>4.1 Symbols .....</b>	<b>7</b>
<b>4.2 Abbreviations .....</b>	<b>7</b>
<b>5 Requirements for pipes and fittings .....</b>	<b>8</b>
<b>5.1 Materials, manufacture, water absorption and appearance .....</b>	<b>8</b>
<b>5.2 Internal diameter .....</b>	<b>8</b>
<b>5.3 Length .....</b>	<b>9</b>
<b>5.4 Squareness of ends .....</b>	<b>9</b>
<b>5.5 Deviation from straightness .....</b>	<b>9</b>
<b>5.6 Water seal of trapped fittings .....</b>	<b>9</b>
<b>5.7 Angle of curvature and radius of bends .....</b>	<b>10</b>
<b>5.8 Branch angle of junctions .....</b>	<b>10</b>
<b>5.9 Crushing strength (FN) .....</b>	<b>10</b>
<b>5.10 Bending tensile strength .....</b>	<b>12</b>
<b>5.11 Bending moment resistance (BMR) .....</b>	<b>12</b>
<b>5.12 Bond strength of adhesive used for fixing fired clay parts together .....</b>	<b>12</b>
<b>5.13 Fatigue strength under cyclic load .....</b>	<b>13</b>
<b>5.14 Watertightness of pipes and junctions .....</b>	<b>13</b>
<b>5.15 Chemical resistance .....</b>	<b>13</b>
<b>5.16 Hydraulic roughness .....</b>	<b>13</b>
<b>5.17 Abrasion resistance .....</b>	<b>13</b>
<b>5.18 Airtightness .....</b>	<b>13</b>
<b>5.19 Tightness of fittings .....</b>	<b>14</b>
<b>5.20 Resistance against high pressure water jetting .....</b>	<b>14</b>
<b>6 Requirements for joints and joint assemblies .....</b>	<b>15</b>
<b>6.1 Joint materials .....</b>	<b>15</b>
<b>6.2 Watertightness of joint assemblies under deflection and shear load .....</b>	<b>16</b>
<b>6.3 Continuity of invert in joint assemblies .....</b>	<b>17</b>
<b>6.4 Joint interchangeability of pipes and fittings in joint assemblies .....</b>	<b>17</b>
<b>6.5 Chemical and physical resistance to effluent of joint assemblies .....</b>	<b>19</b>
<b>6.6 Thermal cycling stability of joint assemblies .....</b>	<b>20</b>
<b>6.7 Long-term thermal stability of joint assemblies .....</b>	<b>20</b>
<b>7 Common requirements for pipes, fittings and joints .....</b>	<b>20</b>
<b>7.1 Reaction to fire .....</b>	<b>20</b>
<b>7.2 Durability .....</b>	<b>20</b>
<b>7.3 Dangerous substances .....</b>	<b>21</b>
<b>8 Designation .....</b>	<b>21</b>
<b>9 Marking .....</b>	<b>21</b>

<b>9.1</b>	<b>Pipes and fittings .....</b>	<b>21</b>
<b>9.2</b>	<b>Joints .....</b>	<b>22</b>
<b>10</b>	<b>Evaluation of conformity .....</b>	<b>22</b>
<b>10.1</b>	<b>General .....</b>	<b>22</b>
<b>10.2</b>	<b>Initial type testing .....</b>	<b>22</b>
<b>10.3</b>	<b>Factory production control (FPC) .....</b>	<b>22</b>
<b>Annex A (normative) Requirements for vitrified clay fittings .....</b>		<b>23</b>
<b>Annex B (informative) Guidance on design, installation and operation of sewers and drains constructed from vitrified clay pipes .....</b>		<b>24</b>
<b>B.1</b>	<b>General .....</b>	<b>24</b>
<b>B.2</b>	<b>Hydraulic design .....</b>	<b>24</b>
<b>B.3</b>	<b>Structural design .....</b>	<b>24</b>
<b>B.4</b>	<b>Installation .....</b>	<b>24</b>
<b>B.5</b>	<b>Operation and maintenance .....</b>	<b>24</b>
<b>B.6</b>	<b>Economy .....</b>	<b>25</b>
<b>B.7</b>	<b>Environmental characteristics .....</b>	<b>25</b>
<b>Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive .....</b>		<b>26</b>
<b>Z.A.1 Scope and relevant characteristics .....</b>		<b>26</b>
<b>Z.A.2 Procedures for the attestation of conformity of vitrified clay pipes, fittings and pipe joints .....</b>		<b>28</b>
<b>Z.A.3 CE marking .....</b>		<b>29</b>
<b>Bibliography .....</b>		<b>34</b>