

# DIN EN 295-7:2013-05 (E)

## Vitrified clay pipe systems for drains and sewers - Part 7: Requirements for pipes and joints for pipe jacking

---

Contents	Page
<b>Foreword .....</b>	<b>4</b>
<b>1 Scope .....</b>	<b>6</b>
<b>2 Normative references .....</b>	<b>6</b>
<b>3 Terms and definitions .....</b>	<b>6</b>
<b>4 Requirements for pipes for pipe jacking .....</b>	<b>6</b>
<b>4.1 Materials, manufacture, water absorption and appearance .....</b>	<b>6</b>
<b>4.2 Dimensions .....</b>	<b>7</b>
<b>4.2.1 General .....</b>	<b>7</b>
<b>4.2.2 Internal diameter .....</b>	<b>7</b>
<b>4.2.3 Tolerance on the declared internal diameter .....</b>	<b>7</b>
<b>4.2.4 Continuity of invert .....</b>	<b>8</b>
<b>4.2.5 External diameter .....</b>	<b>8</b>
<b>4.2.6 Length .....</b>	<b>9</b>
<b>4.2.7 Squareness of ends .....</b>	<b>9</b>
<b>4.2.8 Deviation from straightness .....</b>	<b>9</b>
<b>4.3 Strength .....</b>	<b>9</b>
<b>4.3.1 Crushing strength (FN) .....</b>	<b>9</b>
<b>4.3.2 Bending tensile strength .....</b>	<b>10</b>
<b>4.3.3 Compressive strength .....</b>	<b>10</b>
<b>4.3.4 Jacking strength .....</b>	<b>10</b>
<b>4.3.5 Maximum working jacking load .....</b>	<b>11</b>
<b>4.3.6 Fatigue strength under cyclic load .....</b>	<b>11</b>
<b>4.4 Watertightness .....</b>	<b>11</b>
<b>4.5 Airtightness .....</b>	<b>11</b>
<b>4.6 Chemical resistance .....</b>	<b>12</b>
<b>4.7 Hydraulic roughness .....</b>	<b>12</b>
<b>4.8 Abrasion resistance .....</b>	<b>12</b>
<b>4.9 Resistance against high pressure water jetting .....</b>	<b>13</b>
<b>5 Requirements for joints for pipe jacking .....</b>	<b>13</b>
<b>5.1 Joint materials .....</b>	<b>13</b>
<b>5.1.1 Rubber sealing elements .....</b>	<b>13</b>
<b>5.1.2 Polyurethane sealing elements .....</b>	<b>13</b>
<b>5.1.3 Stainless steel sleeves .....</b>	<b>13</b>
<b>5.1.4 Polypropylene sleeve couplings .....</b>	<b>13</b>
<b>5.1.5 Other materials .....</b>	<b>13</b>
<b>5.2 Load transfer rings .....</b>	<b>13</b>
<b>5.3 Watertightness of joints under deflection and shear load .....</b>	<b>14</b>
<b>5.3.1 General .....</b>	<b>14</b>
<b>5.3.2 Test pressures .....</b>	<b>14</b>
<b>5.4 Angular deflection .....</b>	<b>14</b>
<b>5.5 Shear resistance .....</b>	<b>14</b>
<b>5.6 Chemical and physical resistance to effluent .....</b>	<b>14</b>
<b>5.7 Thermal cycling stability .....</b>	<b>15</b>
<b>5.8 Long-term thermal stability .....</b>	<b>15</b>
<b>6 Common requirements for pipes and joints .....</b>	<b>15</b>

<b>6.1</b>	<b>Reaction to fire .....</b>	<b>15</b>
<b>6.2</b>	<b>Durability .....</b>	<b>15</b>
<b>6.3</b>	<b>Dangerous substances .....</b>	<b>16</b>
<b>7</b>	<b>Designation .....</b>	<b>16</b>
<b>8</b>	<b>Marking .....</b>	<b>16</b>
<b>9</b>	<b>Evaluation of conformity .....</b>	<b>17</b>
<b>9.1</b>	<b>General .....</b>	<b>17</b>
<b>9.2</b>	<b>Initial type testing .....</b>	<b>17</b>
<b>9.3</b>	<b>Factory production control (FPC) .....</b>	<b>17</b>
<b>Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive .....</b>		<b>18</b>
<b>Z.A.1</b>	<b>Scope and relevant characteristics .....</b>	<b>18</b>
<b>Z.A.2 Procedures for the attestation of conformity of vitrified clay pipes and joints for pipe jacking .</b>		<b>20</b>
<b>Z.A.2.1</b>	<b>Systems of attestation of conformity .....</b>	<b>20</b>
<b>Z.A.2.2</b>	<b>EC declaration of conformity .....</b>	<b>21</b>
<b>Z.A.3</b>	<b>CE marking .....</b>	<b>21</b>
<b>Z.A.3.1</b>	<b>General .....</b>	<b>21</b>
<b>Z.A.3.2</b>	<b>CE marking on the product .....</b>	<b>21</b>
<b>Z.A.3.3</b>	<b>CE marking in the accompanying documents .....</b>	<b>22</b>
<b>Bibliography .....</b>		<b>25</b>