

# DIN EN 295-5:2013-05 (E)

## Vitrified clay pipe systems for drains and sewers - Part 5: Requirements for perforated pipes and fittings

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
1	Scope .....	4
2	Normative references .....	4
3	Terms and definitions .....	4
4	Requirements for pipes and fittings .....	4
4.1	Material, manufacture, water absorption and appearance .....	4
4.2	Internal diameter .....	4
4.3	Length .....	5
4.4	Deviation from straightness .....	5
4.5	Angle of curvature and radius of bends .....	5
4.6	Branch angle of junctions .....	6
4.7	Perforations .....	6
4.7.1	General .....	6
4.7.2	Arrangement of perforations .....	6
4.7.3	Area of perforations .....	6
4.8	Crushing strength (FN) .....	6
4.9	Chemical resistance .....	7
4.10	Fatigue strength under cyclic load .....	8
5	Joint assemblies .....	8
6	Common requirements for pipes and fittings .....	8
6.1	Reaction to fire .....	8
6.2	Durability .....	8
6.3	Dangerous substances .....	8
7	Designation .....	9
8	Marking .....	9
9	Evaluation of conformity .....	10
9.1	General .....	10
9.2	Initial type testing .....	10
9.3	Factory production control (FPC) .....	10
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of the EU Construction Products Directive .....		11
ZA.1 Scope and relevant characteristics .....		11
ZA.2 Procedures for the attestation of conformity of perforated vitrified clay pipes and fittings .....		12
ZA.2.1 Systems of attestation of conformity .....		12
ZA.2.2 EC declaration of conformity .....		13
ZA.3 CE marking .....		14

<b>ZA.3.1 General .....</b>	<b>14</b>
<b>ZA.3.2 CE marking on the product .....</b>	<b>14</b>
<b>ZA.3.3 CE marking in the accompanying documents .....</b>	<b>15</b>
<b>Bibliography .....</b>	<b>17</b>