DIN EN 295-5:2013-05 (E)

Vitrified clay pipe systems for drains and sewers - Part 5: Requirements for perforated pipes and fittings

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Requirements for pipes and fittings 4
4.1 Material, manufacture, water absorption and appearance 4
4.2 Internal diameter 4
4.3 Length 5
4.4 Deviation from straightness 5
4.5 Angle of curvature and radius of bends 5
4.6 Branch angle of junctions 6
4.7 Perforations 6
4.7.1 General 6
4.7.2 Arrangement of perforations 6
4.7.3 Area of perforations 6
4.8 Crushing strength (FN) 6
4.9 Chemical resistance 7
4.10 Fatigue strength under cyclic load 8

5 Joint assemblies 8

6 Common requirements for pipes and fittings 8
6.1 Reaction to fire 8
6.2 Durability 8
6.3 Dangerous substances 8

7 Designation 9

8 Marking 9

9 Evaluation of conformity 10
9.1 General 10
9.2 Initial type testing 10
9.3 Factory production control (FPC) 10

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of the EU Construction Products Directive 11

ZA.1 Scope and relevant characteristics 11

ZA.2 Procedures for the attestation of conformity of perforated vitrified clay pipes and fittings 12

ZA.2.1 Systems of attestation of conformity 12

ZA.2.2 EC declaration of conformity 13

ZA.3 CE marking 14

ZA.3.1 General 14

ZA.3.2 CE marking on the product 14

ZA.3.3 CE marking in the accompanying documents 15

Bibliography 17