

DIN EN 1796:2013-05 (E)

Plastics piping systems for water supply with or without pressure - Glass-reinforced the rmosetting plastics (GRP) based on unsaturated polyester resin (UP)

Contents		Page
Foreword		5
Introduction		6
1	Scope	7
2	Normative references	8
3	Terms, definitions and symbols	9
4	General requirements	16
4.1	Classification	16
4.1.1	General	16
4.1.2	Categories	16
4.1.3	Nominal size	16
4.1.4	Nominal stiffness	16
4.1.5	Nominal pressure	16
4.2	Materials	17
4.2.1	General	17
4.2.2	Reinforcement	17
4.2.3	Resin	17
4.2.4	Aggregates and fillers	18
4.2.5	Elastomers	18
4.2.6	Metals	18
4.3	Wall construction	18
4.3.1	Inner layer	18
4.3.2	Structural layer	18
4.3.3	Outer layer	18
4.4	Appearance	18
4.5	Reference conditions for testing	19
4.5.1	Temperature	19
4.5.2	Properties of water for testing	19
4.5.3	Loading conditions	19
4.5.4	Preconditioning	19
4.5.5	Measurement of dimensions	19
4.6	Elapsed time for determination of long-term properties, (x)	19
4.7	Joints	19
4.7.1	General	19
4.7.2	Types of joint	19
4.7.3	Flexibility of the jointing system	19
4.7.4	Sealing ring	20
4.7.5	Adhesives	20
5	Pipes	20
5.1	Geometrical characteristics	20
5.1.1	Diameter	20
5.1.2	Wall thickness	25
5.1.3	Length	25
5.2	Mechanical characteristics	26
5.2.1	Initial specific ring stiffness	26
5.2.2	Long-term specific ring stiffness under wet conditions	27

5.2.3	Initial resistance to failure in a deflected condition	28
5.2.4	Ultimate long-term resistance to failure in a deflected condition	30
5.2.5	Initial specific longitudinal tensile strength	31
5.2.6	Initial failure and design pressures for pressure pipes	33
5.2.7	Long-term failure pressure	35
5.3	Marking	36
6	Fittings	37
6.1	General	37
6.2	Bends	38
6.2.1	Classification of bends	38
6.2.2	Dimensions and tolerances of bends	38
6.3	Branches	41
6.3.1	Classification of branches	41
6.3.2	Dimensions and tolerances of branches	42
6.4	Reducers	44
6.4.1	Classification of reducers	44
6.4.2	Dimensions and tolerances of reducers	45
6.4.3	Mechanical characteristics of tapered section laminate	46
6.5	Non Pressure Saddles	47
6.5.1	Classification of saddles	47
6.5.2	Dimensions and tolerances of saddles	48
6.6	Flanges	48
6.6.1	Classification of flanges	48
6.6.2	Dimensions and tolerances for flanged adaptors	49
6.7	Marking	51
7	Joint performance	52
7.1	General	52
7.1.1	Interchangeability	52
7.1.2	Test temperature	52
7.1.3	Non-pressure piping	52
7.2	Dimensions	52
7.3	Non-end-load-bearing flexible joints with elastomeric sealing rings	52
7.3.1	General	52
7.3.2	Requirements	52
7.3.3	Number of test pieces for type test purposes	53
7.3.4	Test pieces	53
7.4	End-load-bearing flexible joints with elastomeric sealing rings	54
7.4.1	General	54
7.4.2	Performance requirements for locked-socket-and-spigot joints with elastomeric sealing rings	54
7.5	Wrapped or cemented joints	56
7.5.1	General	56
7.5.2	Performance requirements	56
7.5.3	Number of test pieces for type test purposes	57
7.5.4	Test pieces	57
7.6	Bolted flange joints	58
7.6.1	General	58
7.6.2	Performance requirements	58
7.6.3	Number of test pieces for type test purposes	59
7.6.4	Test pieces	59
7.6.5	Joint assembly details	59
7.6.6	Torque resistance	59
Annex A (normative)	Test method for the resistance to bending and pressure of end-thrust loaded joints in pipe systems	61
A.1	Principle	61
A.2	Apparatus	61
A.3	Test pieces	62
A.4	Test temperature	62
A.5	Calculation of the bending load F	62

A.5.1	General	62
A.5.2	Calculation of F, if applied in the horizontal plane	62
A.5.3	Calculation of F, if applied in the vertical plane	63
A.6	Procedure	64
A.7	Test report	64
Bibliography		66