ISO 4377:2012-08 (E)

Hydrometric determinations - Flow measurement in open channels using structures - Flat-V weirs

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols 3

5 Characteristics of flat-V weirs 4

6 Installation 4
6.1 Selection of site 4
6.2 Installation conditions 7
6.3 Weir structure 8
6.4 Downstream conditions 8

7 Maintenance 8

8 Measurement of head(s) 9
8.1 General 9
8.2 Stilling (gauge) wells 9
8.3 Zero setting 11
8.4 Location of head measurement sections 13

9 Discharge relationships 14
9.1 Equations of discharge 14
9.2 Effective heads 15
9.3 Shape factors 16
9.4 Coefficient of velocity 16
9.5 Conditions for modular/drowned flow 18
9.6 Drowned flow reduction factor 21
9.7 Limits of application 28

10 Computation of discharge 29
10.1 General 29
10.2 Successive approximation method 29
10.3 Coefficient of velocity method 31
10.4 Accuracy 32

11 Uncertainties in flow determination 32
11.1 General 32
11.2 Combining uncertainties 33
11.3 Uncertainty in the discharge coefficient u*(CDe)68 for the flat-V weir 34
11.4 Uncertainty in the drowned flow reduction factor u*(Cdr) 34
11.5 Uncertainty in the effective head 35
11.6 Uncertainty budget 35
11.7 Variation of uncertainty with flow and uncertainty in mean daily flow and the daily flow volume 36

12 Examples 37
12.1 Example 1 -- Computation of modular flow at low discharge 37
12.2 Example 1 -- Uncertainty in computed discharge 39
12.3 Example 2 -- Computation of drowned flow at high discharge 41
12.4 Example 2 -- Uncertainty in computed discharge 43

Annex A (normative) Velocity distribution 46

Annex B (informative) Introduction to measurement uncertainty 47

Annex C (informative) Performance guide for hydrometric equipment for use in technical standards 56

Bibliography 59