

DIN EN 12201-3:2013-01 (E)

Plastics piping systems for water supply, and for drainage and sewerage under pressure - Polyethylene (PE) - Part 3: Fittings (includes Amendment A1:2012)

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 4 |
| Introduction | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions, symbols and abbreviations | 9 |
| 4 | Material | 10 |
| 4.1 | PE compound | 10 |
| 4.2 | Material for non-polyethylene parts | 10 |
| 4.2.1 | General | 10 |
| 4.2.2 | Metal parts | 11 |
| 4.2.3 | Elastomers | 11 |
| 4.2.4 | Other materials | 11 |
| 5 | General characteristics | 11 |
| 5.1 | Appearance | 11 |
| 5.2 | Design | 11 |
| 5.3 | Colour | 11 |
| 5.4 | Electrical characteristics for electrofusion fittings | 11 |
| 5.5 | Appearance of factory made joints | 12 |
| 5.6 | Effect on water quality | 12 |
| 6 | Geometrical characteristics | 12 |
| 6.1 | Measurement of dimensions | 12 |
| 6.2 | Dimensions of electrofusion socket fittings | 12 |
| 6.2.1 | Diameters and lengths of electrofusion sockets | 12 |
| 6.2.2 | Wall thicknesses | 14 |
| 6.2.3 | Out-of-roundness of the bore of a fitting (at any point) | 15 |
| 6.3 | Dimensions of spigot end fittings | 15 |
| 6.4 | Dimensions of socket fusion fittings | 17 |
| 6.5 | Dimensions of electrofusion saddle fittings | 17 |
| 6.6 | Dimensions of mechanical fittings | 18 |
| 6.7 | Dimensions of loose backing flanges and flange adapters | 18 |
| 6.8 | Dimensions of fabricated fittings | 18 |
| 7 | Mechanical characteristics | 18 |
| 7.1 | General | 18 |
| 7.2 | Conditioning | 19 |
| 7.3 | Requirements | 19 |
| 7.4 | Retest in case of failure at 80 °C | 21 |
| 7.5 | Pressure drop | 21 |
| 7.6 | Performance requirements | 21 |
| 8 | Physical characteristics | 22 |
| 8.1 | Conditioning | 22 |
| 8.2 | Requirements | 22 |

| | | |
|--|---|----|
| 9 | Chemical resistance of fittings in contact with chemicals | 22 |
| 10 | Performance requirements | 22 |
| 11 | Marking | 23 |
| 11.1 | General | 23 |
| 11.2 | Minimum required marking of fittings | 23 |
| 11.3 | Additional marking | 24 |
| 11.4 | Fusion system recognition | 24 |
| 12 | Delivery Conditions | 24 |
| Annex A (normative) Socket fusion fittings | | 25 |
| Annex B (normative) Fabricated fittings | | 27 |
| B.1 | General | 27 |
| B.2 | Dimensions | 28 |
| B.3 | Segmented bends | 29 |
| B.4 | Swept bends | 31 |
| B.5 | Segmented tees | 32 |
| Annex C (informative) Examples of typical terminal connection for electrofusion fittings | | 34 |
| Annex D (normative) Short-term pressure test method | | 37 |
| D.1 | Principle | 37 |
| D.2 | Apparatus | 37 |
| D.3 | Test piece | 37 |
| D.4 | Procedure | 37 |
| D.5 | Test report | 38 |
| Annex E (normative) Tensile test for fitting/pipe assemblies | | 39 |
| E.1 | Principle | 39 |
| E.2 | Apparatus | 39 |
| E.3 | Test piece | 39 |
| E.4 | Procedure | 39 |
| E.5 | Test report | 39 |
| Bibliography | | 41 |