

DIN EN ISO 11297-3:2013-11 (E)

Plastics piping systems for renovation of underground drainage and sewerage networks under pressure - Part 3: Lining with clos e-fit pipes (ISO 11297-3:2013)

Contents	Page
Foreword	3
Introduction	4
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
3.1 General	7
3.2 Techniques	7
3.3 Characteristics	7
3.4 Materials	7
3.5 Product stages	7
3.6 Service conditions	8
3.7 Joints	8
4 Symbols and abbreviated terms	9
4.1 Symbols	9
4.2 Abbreviated terms	9
5 Pipes at the "M" stage	9
5.1 Materials	9
5.2 General characteristics	10
5.3 Material characteristics	10
5.4 Geometric characteristics	10
5.5 Mechanical characteristics	10
5.6 Physical characteristics	10
5.7 Jointing	10
5.8 Marking	10
6 Fittings at the "M" stage	11
7 Ancillary components	11
8 Fitness for purpose of the installed lining system at the "I" stage	11
8.1 Materials	11
8.2 General characteristics	11
8.3 Material characteristics	11
8.4 Geometric characteristics	11
8.5 Mechanical characteristics	12
8.6 Physical characteristics	13
8.7 Additional characteristics	13
8.8 Sampling	14
9 Installation practice	14
9.1 Preparatory work	14
9.2 Storage, handling and transport of pipes and fittings	14
9.3 Equipment	14
9.4 Installation	16
9.5 Process-related inspection and testing	17

Annex A (normative) Factory-folded heat-reverted polyethylene (PE) pipe -- Determination of memory ability	18
Bibliography	19