

ISO 11297-3:2013-06 (E)

Plastics piping systems for renovation of underground drainage and sewerage networks under pressure - Part 3: Lining with close-fit pipes

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	General	2
3.2	Techniques	2
3.3	Characteristics	2
3.4	Materials	2
3.5	Product stages	2
3.6	Service conditions	3
3.7	Joints	3
4	Symbols and abbreviated terms	4
4.1	Symbols	4
4.2	Abbreviated terms	4
5	Pipes at the "M" stage	4
5.1	Materials	4
5.2	General characteristics	5
5.3	Material characteristics	5
5.4	Geometric characteristics	5
5.5	Mechanical characteristics	5
5.6	Physical characteristics	5
5.7	Jointing	5
5.8	Marking	5
6	Fittings at the "M" stage	6
7	Ancillary components	6
8	Fitness for purpose of the installed lining system at the "I" stage	6
8.1	Materials	6
8.2	General characteristics	6
8.3	Material characteristics	6
8.4	Geometric characteristics	6
8.5	Mechanical characteristics	7
8.6	Physical characteristics	8
8.7	Additional characteristics	8
8.8	Sampling	9
9	Installation practice	9
9.1	Preparatory work	9
9.2	Storage, handling and transport of pipes and fittings	9
9.3	Equipment	9
9.4	Installation	11
9.5	Process-related inspection and testing	12

Annex A (normative) Factory-folded heat-reverted polyethylene (PE) pipe -- Determination of memory ability	13
Bibliography	15