

# DIN 4925-3:2014-09 (E)

## Well screens and casings of unplasticized polyvinylchloride (PVC-U) for tube well - Part 3: DN 250 to DN 400 with trapezoidal thread

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
1	<b>Scope .....</b>	<b>4</b>
2	<b>Normative references .....</b>	<b>4</b>
3	<b>Dimensions and masses, slot pattern, designation .....</b>	<b>4</b>
3.1	<b>Dimensions and masses .....</b>	<b>4</b>
3.2	<b>Slot pattern .....</b>	<b>7</b>
3.3	<b>Designation .....</b>	<b>7</b>
4	<b>Material (moulding compound) .....</b>	<b>8</b>
5	<b>General requirements .....</b>	<b>8</b>
6	<b>Hygiene requirements .....</b>	<b>8</b>
7	<b>Threaded joint .....</b>	<b>8</b>
7.1	<b>Thread profile .....</b>	<b>8</b>
7.2	<b>Dimensions .....</b>	<b>10</b>
7.3	<b>Designation .....</b>	<b>10</b>
8	<b>Seals .....</b>	<b>10</b>
8.1	<b>General .....</b>	<b>10</b>
8.2	<b>Dimensions .....</b>	<b>11</b>
8.3	<b>Designation .....</b>	<b>11</b>
Bibliography .....		12