

# ISO 26906:2015-10 (E)

## Hydrometry - Fishpasses at flow measurement structures

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols .....</b>	<b>2</b>
<b>5</b>	<b>Principle .....</b>	<b>4</b>
<b>6</b>	<b>Installation .....</b>	<b>4</b>
<b>6.1</b>	<b>Requirements for gauging structure and fishpass installations .....</b>	<b>4</b>
<b>6.1.1</b>	<b>Selection of site .....</b>	<b>4</b>
<b>6.1.2</b>	<b>Installation conditions .....</b>	<b>5</b>
<b>6.1.3</b>	<b>Upstream channel .....</b>	<b>6</b>
<b>6.1.4</b>	<b>Separate channel .....</b>	<b>6</b>
<b>6.1.5</b>	<b>Downstream channel .....</b>	<b>7</b>
<b>6.1.6</b>	<b>Flow measurement and fishpass structures .....</b>	<b>7</b>
<b>6.1.7</b>	<b>Maintenance .....</b>	<b>7</b>
<b>6.1.8</b>	<b>Measurement of head .....</b>	<b>8</b>
<b>6.2</b>	<b>Requirements specific to the fishpass .....</b>	<b>8</b>
<b>6.2.1</b>	<b>General .....</b>	<b>8</b>
<b>6.2.2</b>	<b>Guidelines for basic parameters of fishpasses .....</b>	<b>9</b>
<b>6.2.3</b>	<b>Location and attraction flows .....</b>	<b>9</b>
<b>6.2.4</b>	<b>Downstream entry/exit to fishpass .....</b>	<b>9</b>
<b>6.2.5</b>	<b>Upstream exit/entry from fishpass .....</b>	<b>10</b>
<b>7</b>	<b>Fishpass performance .....</b>	<b>10</b>
<b>7.1</b>	<b>General .....</b>	<b>10</b>
<b>7.1.1</b>	<b>Types .....</b>	<b>10</b>
<b>7.1.2</b>	<b>Fishpasses with interconnected pools .....</b>	<b>10</b>
<b>7.1.3</b>	<b>Fishpasses with continuous energy dissipation .....</b>	<b>10</b>
<b>7.1.4</b>	<b>Calibration and discharge coefficient .....</b>	<b>11</b>
<b>7.2</b>	<b>Larinier super-active baffle fishpass with baffle sizes between 75 mm and 150 mm .....</b>	<b>11</b>
<b>7.2.1</b>	<b>Description .....</b>	<b>11</b>
<b>7.2.2</b>	<b>The following features apply to the range of baffle sizes from 75 mm to 150 mm .....</b>	<b>12</b>
<b>7.2.3</b>	<b>Limitations .....</b>	<b>13</b>
<b>7.2.4</b>	<b>Modular flow calibration .....</b>	<b>14</b>
<b>7.2.5</b>	<b>Modular limit .....</b>	<b>15</b>
<b>7.3</b>	<b>Pool-type fishpass with V-shaped overfalls .....</b>	<b>15</b>
<b>7.3.1</b>	<b>Description .....</b>	<b>15</b>
<b>7.3.2</b>	<b>Determination of discharge under free flow conditions .....</b>	<b>18</b>
<b>7.3.3</b>	<b>Modular limit .....</b>	<b>21</b>
<b>7.3.4</b>	<b>Determination of discharge under submerged flow conditions .....</b>	<b>22</b>
<b>7.3.5</b>	<b>Limitations .....</b>	<b>23</b>
<b>7.3.6</b>	<b>Scaling up to standard design .....</b>	<b>23</b>
<b>7.4</b>	<b>Dutch pool and orifice fishpass .....</b>	<b>23</b>
<b>7.4.1</b>	<b>Description .....</b>	<b>23</b>

7.4.2	Determination of discharge .....	25
7.4.3	Scaling up the standard design .....	27
8	Computation of discharge .....	27
8.1	Principles .....	27
8.2	Details .....	28
9	Uncertainties in flow determination .....	28
9.1	General .....	28
9.2	Combining uncertainties .....	29
9.3	Uncertainty in the discharge coefficient $u^*(CDe)_{68}$ for the fish-pass .....	30
9.4	Uncertainty in the effective head .....	30
9.5	Uncertainty budget .....	30
9.5.1	General .....	30
9.5.2	Compound structures - sources of uncertainty .....	31
10	Example .....	31
10.1	Installation .....	31
10.2	Flow conditions .....	32
10.3	Computation of discharge .....	32
10.3.1	Modularity .....	32
10.3.2	Flow over the flat-V weir .....	32
10.3.3	Flow through the fish-pass .....	33
10.3.4	Total flow .....	33
10.3.5	Uncertainty in flow through the fish-pass .....	33
10.3.6	Uncertainty in flow over the flat-V weir .....	34
10.3.7	Uncertainty in total flow .....	34
10.3.8	Reduction in overall uncertainty if second head gauge were to be installed upstream of the fish-pass .....	34
	Annex A (informative) Introduction to measurement uncertainty .....	35
	Annex B (informative) Performance guide for hydrometric equipment for use in technical standards .....	44
	Bibliography .....	48