

DIN EN ISO 11296-2:2018-09 (Englis ch)

Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks - Part 2: Lining with continuous pipes (ISO 11296-2:2018)

Contents	Page
European foreword	3
Foreword	4
Introduction	5
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols and abbreviated terms	8
4.1 Symbols	8
4.2 Abbreviated terms	8
5 Pipes at the "M" stage	8
5.1 Material	8
5.2 General characteristics	8
5.3 Material characteristics	9
5.4 Geometrical characteristics	9
5.5 Mechanical characteristics	9
5.6 Physical characteristics	9
5.7 Jointing	9
5.8 Marking	9
5.9 Regional requirements for pipes	9
6 Fittings at the "M" stage	9
6.1 Requirements	9
6.2 Marking	9
6.3 Regional requirements for fittings	9
7 Ancillary components	9
8 Fitness for purpose of the system for pipes and fittings at the "I" stage	10
9 Installation practice	10
9.1 Preparatory work	10
9.2 Storage, handling and transport	10
9.3 Equipment	10
9.3.1 Butt fusion equipment and de-beading equipment	10
9.3.2 Pipe rollers	11
9.3.3 Winching and rod-pulling equipment	11
9.3.4 Pipe entry guides	11
9.3.5 Electrofusion equipment	11
9.3.6 Inspection equipment	11
9.3.7 Lifting equipment	11
9.4 Installation	11
9.5 Process-related inspection and testing	12
9.6 Lining termination	12
9.7 Reconnection to the existing pipeline system	12
9.8 Final inspection and testing	12
9.9 Documentation	12
Annex A (normative) Layered pipes	13
Bibliography	14