

ISO 11297-2:2018-02 (E)

Plastics piping systems for renovation of underground drainage and sewerage networks under pressure - Part 2: Lining with continuous pipes

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	2
4.1	Symbols	2
4.2	Abbreviated terms	3
5	Pipes at the "M" stage	3
5.1	Material	3
5.2	General characteristics	3
5.3	Material characteristics	3
5.4	Geometrical characteristics	3
5.5	Mechanical characteristics	3
5.6	Physical characteristics	3
5.7	Jointing	3
5.8	Marking	3
5.9	Regional requirements for pipes	4
6	Fittings at the "M" stage	4
6.1	Requirements	4
6.2	Marking	4
6.3	Regional requirements for fittings	4
7	Ancillary components	4
8	Fitness for purpose of the system for pipes and fittings at the "I" stage	4
9	Installation practice	4
9.1	Preparatory work	4
9.2	Storage, handling and transport	4
9.3	Equipment	5
9.3.1	Butt fusion equipment and de-beading equipment	5
9.3.2	Pipe rollers	5
9.3.3	Winching and rod-pulling equipment	5
9.3.4	Pipe entry guides	5
9.3.5	Electrofusion equipment	6
9.3.6	Inspection equipment	6
9.3.7	Lifting equipment	6
9.4	Installation	6
9.5	Process-related inspection and testing	7
9.6	Lining termination	7
9.7	Reconnection to the existing pipeline system	7
9.8	Final inspection and testing	7
9.9	Documentation	7

Annex A (normative) Layered pipes	8
Bibliography	9