

ISO 11298-2:2018-02 (E)

Plastics piping systems for renovation of underground water supply networks - Part 2: Lining with continuous pipes

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviated terms	2
4.1 Symbols	2
4.2 Abbreviated terms	3
5 Pipes at the "M" stage	3
5.1 Material	3
5.2 General characteristics	3
5.3 Material characteristics	3
5.4 Geometrical characteristics	3
5.5 Mechanical characteristics	3
5.6 Physical characteristics	3
5.7 Jointing	3
5.8 Marking	3
5.9 Regional requirements for pipes	4
6 Fittings at the "M" stage	4
6.1 Requirements	4
6.2 Marking	4
6.3 Regional requirements for fittings	4
7 Ancillary components	4
8 Fitness for purpose of the system for pipes and fittings at the "I" stage	4
9 Installation practice	4
9.1 Preparatory work	4
9.2 Storage, handling and transport	4
9.3 Equipment	5
9.3.1 Butt fusion equipment and debeading equipment	5
9.3.2 Pipe rollers	5
9.3.3 Winching and rod-pulling equipment	5
9.3.4 Pipe entry guides	5
9.3.5 Electrofusion equipment	6
9.3.6 Inspection equipment	6
9.3.7 Lifting equipment	6
9.4 Installation	6
9.5 Process-related inspection and testing	7
9.6 Lining termination	7
9.7 Reconnection to the existing pipeline system	7
9.8 Final inspection and testing	7
9.9 Documentation	7

Annex A (normative) Layered pipes	8
Bibliography	9